

## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Bison International B.V.

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e-mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GE

www.griffon.eu 1/14



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

(Contd. of page 1)

#### · Hazard pictograms







GHS02 GHS07 GHS09

### Signal word Danger

#### Hazard-determining components of labelling:

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C6, isoalkanes, <5% n-hexane

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

#### **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P302+P352 IF ON SKIN: Wash with plenty of water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with national regulations.

#### · 2.3 Other hazards

#### · Results of PBT and vPvB assessment

· **PBT**: Not applicable. · vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

Description: Adhesive

	Description: Adnesive		
· Dangerous components:			
	CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-50%
	EC number: 926-605-8 Reg.nr.: 01-2119486291-36- XXXX	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066	≥10-<25%

(Contd. on page 3)

www.griffon.eu 2/14



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

		Contd. of page
EC number: 931-254-9 Reg.nr.: 01-2119484651-34- XXXX	Hydrocarbons, C6, isoalkanes, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥10-<25%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35- XXXX	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥2.5-<10%
EC number: 927-510-4 Reg.nr.: 01-2119475515-33- XXXX	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	≥2.5-<10%
CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1 Reg.nr.: 01-2119463273-41- XXXX	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	≥2.5-<10%
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0 Reg.nr.: 01-2119480412-44- XXXX	n-hexane  Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 Specific concentration limit:  STOT RE 2; H373: C ≥5 %	≥1-<2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information: No special measures required.
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 4)

GB

www.griffon.eu 3/14



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

(Contd. of page 3)

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

110-82-7 cyclohexane

WEL Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm

110-54-3 n-hexane

WEL Long-term value: 72 mg/m³, 20 ppm

(Contd. on page 5)

GΒ

www.griffon.eu 4/14



# Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

DNEL -				(Contd. of p		
DNELs		Secollosses of D. 1997				
	drocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane					
Oral		ral, longterm exposition	1301 mg/kg bw/day (rat)			
Dermal		nal, longterm exposition	13964 mg/kg bw/day (rat)			
		ermal, longterm exposition	1377 mg/kg bw/day (rat)			
Inhalative		lative, longterm exposition	5306 mg/m³ (rat)			
	-	nhalative, longterm exposition	1131 mg/m³ (rat)			
-		alkanes, <5% n-hexane				
Oral		ral, longterm exposition	1301 mg/kg bw/day (rat)			
Dermal		nal, longterm exposition	13964 mg/kg bw/day (rat)			
		ermal, longterm exposition	1377 mg/kg bw/day (rat)			
Inhalative	Worker, inha	lative, longterm exposition	5306 mg/m³ (rat)			
	Consumer, ir	nhalative, longterm exposition	1131 mg/m³ (rat)			
•	•	n-alkanes, isoalkanes, cycli				
Oral	-	ral, longterm exposition	699 mg/kg bw/day (rat)			
Dermal	Worker, derr	nal, longterm exposition	773 mg/kg bw/day (rat)			
	Consumer, d	ermal, longterm exposition	699 mg/kg bw/day (rat)			
Inhalative	Worker, inha	lative, longterm exposition	2035 mg/m³ (rat)			
	Consumer, ir	nhalative, longterm exposition	608 mg/m³ (rat)			
Hydrocarl	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics					
Oral	Consumer, o	ral, longterm exposition	149 mg/kg bw/day (rat)			
Dermal	Worker, derr	nal, longterm exposition	300 mg/kg bw/day (rat)			
	Consumer, d	ermal, longterm exposition	149 mg/kg bw/day (rat)			
Inhalative	Worker, inha	lative, longterm exposition	2085 mg/m³ (rat)			
	Consumer, inhalative, longterm exposition		477 mg/m³ (rat)			
110-82-7 c	yclohexane	<u> </u>	. ,			
Oral	Consumer, o	ral, longterm exposition	59.4 mg/kg bw/day (rat)			
Dermal	Worker, derr	nal, longterm exposition	2016 mg/kg bw/day (rat)			
		ermal, longterm exposition	1186 mg/kg bw/day (rat)			
Inhalative		lative, shortterm exposition	700 mg/m³ (rat)			
		lative, longterm exposition	700 mg/m³ (rat)			
		NEL, acute inhalation	412 mg/m³ (rat)			
		nhalative, longterm exposition	• , ,			
PNECs	, , , , , , , , , , , , , , , , , , ,		, ,			
	yclohexane					
Fresh wate		0.207 mg/l (rat)				
Fresh water sediment 3.627 mg/		3.627 mg/kg dry weight (rat)				
		0.207 mg/l (rat)				
Marine wa Marine sed		3.627 mg/kg dry weight (rat)				
		2.99 mg/kg (rat)				
JUII		2.55 mg/kg (rat)		(Contd. on p		

www.griffon.eu 5/14



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

(Contd. of page 5)

Sewage treatment plant | 3.24 mg/l (rat) Sporadic release | 0.207 mg/l

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

- Recommended filter device for short term use: Filter A
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber, NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

- Eye/face protection Not required.
- Body protection: Use protective suit.

### **SECTION 9: Physical and chemical properties**

• 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and

boiling range 60 °C

(Contd. on page 7)

GB

www.griffon.eu 6/14



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

(Contd. of page 6)

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: 0.7 Vol %
Upper: 18.6 Vol %
Flash point: -42 °C
Auto-ignition temperature: 235 °C

Decomposition temperature: Not determined.pH Mixture is a gas.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log

value) Not determined.
• Vapour pressure at 20 °C: 5200 hPa

Density and/or relative density

Density at 20 °C: ~0.773 g/cm³
Relative density Not determined.
Vapour density Not determined.

• 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the characterization

of the mixture.

· Appearance:

· Form: Aerosol

Important information on protection of health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

Organic solvents: 88.6 %
 VOC (EC) 88.64 %
 Solids content: 13.5 %

Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard

classes

Explosives VoidFlammable gases Void

• Aerosols Extremely flammable aerosol. Pressurised

container: May burst if heated.

Oxidising gases
Gases under pressure
Flammable liquids
Flammable solids

Void
Void

(Contd. on page 8)

- GB

www.griffon.eu 7/14



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

(Contd. of page 7)

		(Oorita. or page 1)
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

### **SECTION 11: Toxicological information**

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

	· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 · Acute toxicity Based on available data, the classification criteria are not met.		
· LD/LC50 v	· LD/LC50 values relevant for classification:		
115-10-6 c	115-10-6 dimethyl ether		
Inhalative	Inhalative LC50/4 h 308 mg/l (rat)		
Hydrocarl	oons, C6-0	C7, isoalkanes, cyclics, <5% n-hexane	
Oral	LD50	>3350 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
Inhalative	LC50/4 h	>20 mg/l (rat)	
Hydrocarl	oons, C6,	isoalkanes, <5% n-hexane	
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>3000 mg/kg (rat)	
Inhalative	LC50/4 h	>20 mg/l (rat)	
Hydrocarl	oons, C6-0	C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
Inhalative	LC50/4 h	>20 mg/l (rat)	
		(Contd. on page 9)	

www.griffon.eu 8/14

, GВ



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

(	Contd.	of	page	8

		(Contd. or page 8)	
Hydrocart	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		
Oral	LD50	>5840 mg/kg (rat)	
Dermal	LD50	>2920 mg/kg (rat)	
Inhalative	LC50/4 h	>23.3 mg/l (rat)	
110-82-7 c	110-82-7 cyclohexane		
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	32.88 mg/l (rat)	
110-54-3 n	ı-hexane		
Oral	LD50	16000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
Inhalative	LC50/4 h	172 mg/l (rat)	

- Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 10)

GB

www.griffon.eu 9/14



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

(Contd. of page 9)

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

## **SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

### **SECTION 14: Transport information**

- · 14.1 UN number or ID number
- · ADR/ADN, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR/ADN 1950 AEROSOLS

· IMDG AEROSOLS, MARINE POLLUTANT

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- · ADR/ADN





· Class 2 5F Gases. · Label 2.1

·IMDG





· Class 2.1 Gases.

(Contd. on page 11)

GE

www.griffon.eu 10/14



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

(Contd. of page 10) · Label 2.1 ·IATA · Class 2.1 Gases. · Label · 14.4 Packing group · ADR/ADN, IMDG, IATA not regulated · 14.5 Environmental hazards: Product contains environmentally hazardous substances: Naphtha (petroleum), hydrotreated light · Marine pollutant: Yes Symbol (fish and tree) Special marking (ADR/ADN): Symbol (fish and tree) · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): · EMS Number: F-D,S-U Stowage Code SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. 14.7 Maritime transport in bulk according to **IMO** instruments Not applicable. · Transport/Additional information: Quantity limitations On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg · ADR/ADN · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity Transport category

www.griffon.eu 11/14

(Contd. on page 12)



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

(	Contd.	of	page	1	1

	(Contd. or page 11)
· Tunnel restriction code	D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	U N 1950 A E R O S O L S , 2 . 1 , ENVIRONMENTALLY HAZARDOUS

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 57
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 13)

www.griffon.eu 12/14

GF



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

(Contd. of page 12)

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Rolevant nhrases

Releval	Relevant phrases		
H220	Extremely flammable gas.		
H225	Highly flammable liquid and vapour.		
H280	Contains gas under pressure; may explode if heated.		
H304	May be fatal if swallowed and enters airways.		
H315	Causes skin irritation.		
H336	May cause drowsiness or dizziness.		
H361f	Suspected of damaging fertility.		
H373	May cause damage to organs through prolonged or repeated exposure.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		

Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008			
Aerosols, Section 2.3.1	Bridging principles		
Skin corrosion/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.		

Department issuing SDS: PSRA

· Contact: PSRA

· Date of previous version: 20.05.2025 · Version number of previous version: 43

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

(Contd. on page 14)

GB

www.griffon.eu 13/14



## Safety data sheet according to UK REACH

Printing date 27.07.2025 Version number 44 (replaces version 43) Revision: 27.07.2025

Trade name: GRF SPRAY ADHESIVE AE 500ML\*12 L221

(Contd. of page 13)

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

\* Data compared to the previous version altered.

GB -

www.griffon.eu 14/14