

½" M NPT SPRINKLER INVERTED INSTALLATION OPTIONS

LOWER FLOWS (Use with 0.270" tubing)				
DROP ASSEMBLY			DROP ADAPTER ASSEMBLY	
DRUA1B23S12	DRASM1/23S23S12	DRLA1B2F12	DRADASM1B2F24	DRADASM123S2F24
FTA1B1B 0.270" Super Barb x Hose Barb 	FTA1B23S 0.270" Super Barb x ½" F / ¾" M Slip 		FTA1B1B 0.270" Super Barb x Hose Barb 	FTA1B23S 0.270" Super Barb x ½" F / ¾" M Slip 
TU1ST1 0.270" I.D 12" Length 	TU1ST1 0.270" I.D 12" Length 		TU1ST1 0.270" I.D 12" Length 	TU1ST1 0.270" I.D 12" Length 
FTA1B23S 0.270" Super Barb x ½" F / ¾" M Slip 	FTA1B23S 0.270" Super Barb x ½" F / ¾" M Slip 	FTA1B23S 0.270" Super Barb x ½" /¾" M Slip 	FTA1B23S 0.270" Super Barb x ½" F / ¾" M Slip 	FTA1B23S 0.270" Super Barb x ½" F / ¾" M Slip 
		RSRP10 ½" PVC 10" Length 	RSRP10 ½" PVC 10" Length 	RSRP10 ½" PVC 10" Length 
		SM0435005 ½" F Slip x ½" F NPT 	SM0435005 ½" F Slip x ½" F NPT 	SM0435005 ½" F Slip x ½" F NPT 