



Description	Use	Specifications
<p>Dosing instructions (practical advice):</p> <ul style="list-style-type: none"> <li>• When the TA value is too low, the pH value can vary greatly. This can cause corrosion or staining</li> <li>• If the TA value is too high, it is very difficult to lower the pH value</li> <li>• The ideal TA value is between 100 and 150 ppm (mg/l). Values higher than 175 and lower than 60 ppm (mg/l) require an adjustment</li> <li>• 150g of this product per 10 m<sup>3</sup> of water increases the TA by 10 ppm (mg/l)</li> <li>• Do not dose more than 300g per 10 m<sup>3</sup> per treatment</li> <li>• During treatment, the pump should be running for 3 to 4 hours</li> <li>• Perform a possible second treatment only 12 hours after the first treatment</li> </ul> <p>Warning:</p> <ul style="list-style-type: none"> <li>• Always read the label and product information before use</li> <li>• Keep in a cool dark place, out of the reach of children</li> <li>• Do not throw the granulate directly into the bath, but dissolve it in a bucket of cool water. Then distribute evenly over the water surface</li> <li>• Never mix with other (swimming pool) chemicals, always add the product to water, never the other way around</li> <li>• To avoid risk of skin and eye irritation, it is recommended to wear protective gloves and eye</li> </ul>		

## Related products

All products →  
[\(https://www.melpool.com/en/products/\)](https://www.melpool.com/en/products/)