## **RAIN-CLIK**<sup>™</sup>

To prevent water waste, built-in Quick Response<sup>™</sup> technology instantly shuts down irrigation as soon as it starts raining.

## **KEY BENEFITS**

- Instant Quick Response rain shutoff and freeze shutoff at 3°C
- · Maintenance-free design with integrated battery for wireless models
- Adjustable vent ring allows for shorter or longer reset period
- Rugged polycarbonate housing and metal extension arm
- Includes gutter bracket and wall mount with wireless models
- · Compatible with most normally open or normally closed irrigation controllers

## **OPERATING SPECIFICATIONS**

- · Quick Response:
  - Time to turn off irrigation system: approximately 2 to 5 minutes for Quick Response
  - Time to reset Quick Response: approximately 4 hours under dry, sunny conditions
  - Time to reset when fully wet: approximately 3 days under dry, sunny conditions
- All models switch rating (24 VAC): 3 A
- Wired models include 7 m of 0.5 mm<sup>2</sup> sheathed, two-conductor, UL-approved wire
- Wireless model operating frequency: 433 MHz
- Wireless model range is 243 m line of sight from sensor to receiver
- · Multiple wireless receivers can be operated from a single wireless sensor
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

RAIN-CLIK	
Model	Description
RAIN-CLIK	Wired Rain-Clik sensor
RFC	Wired Rain/Freeze-Clik sensor
WR-CLIK	Wireless Rain-Clik sensor and receiver
WRF-CLIK	Wireless Rain/Freeze-Clik sensor and receiver
SGM	Optional gutter mount (included with WR-CLIK and WRF-CLIK)
WS-GUARD	Vandal-resistant wireless sensor guard for flat surfaces or pole mounting (order sensor separately)
WR-GUARD	Vandal-resistant wireless receiver guard for pedestal mounting (order receiver separately)



Sensor: Rain, Freeze



RAIN-CLIK/RFC (with mounting arm) Height: 6 cm Length: 18 cm

**SGM** Height: 1.2 cm Length: 7.6 cm



WR-CLIK/WRF-CLIK (with mounting arm) Height: 7.6 cm Length: 20 cm



Wireless Receiver (with mounting hardware) Height: 8.3 cm Length: 10 cm



Wireless Sensor Guard (with mounting hardware) Height: 7 cm Length: 9.5 cm Depth: 3.2 cm



: -



Smart WaterMark Recognised as a responsible water-saving tool