

# **EURO TRIX®**

# The versatile water hose

### **Application**

EURO TRIX® water hose is a product for universal operation. It is designed for safe operation in mobile or stationary hose lines in industry and construction as well as farming, landscape gardening, municipal facilities, car pools etc. The hose is highly flexible, robust and easy to handle.

#### Marking

6 orange stripes, axially applied, on black cover "Continental ContiTech EURO TRIX" DN 13 PN 15 BAR / 218 PSI Made in Germany"


#### Description

- > Black, non-porous and smooth EPDM lining
- > Reinforcements: synthetic fibres
- > Black, smooth EPDM-cover, resistant to ozone, weather and UV
- > Working pressure up to 15 bar / 218 psi
- > Temperature range from -20°C up to +100°C / -4°F up to +212°F
- > Highly flexible, twist-free and non-buckling
- > Release agent- and fat-free, free from any product harmful to lacquer

## Technical data

nominal width	inner-Ø	wall thickness	length	working pressure		min. burst pressure		min. bending radius	weight
zoll/inch	mm	mm	m	bar	psi	bar	psi	aprx. mm	aprx. g/m
1/2	13	3.5	40	(15)	218	45	653	50	265
5/8	16	3.8	40	15	218	45	653	65	360
3/4	19	4.0	40	(15)	218	45	653	70	435
1	25	4.5	40	(15)	218	45	653	120	580

 $Pressure\ based\ on\ room\ temperature\ /\ High\ pressure\ and/or\ temperature\ lead\ to\ reduced\ component\ durability$ 



industrial hoses@fluid.contitech.de

ContiTech Schlauch GmbH Continentalstraße 3-5 | 34497 Korbach, Germany www.contitech.de www.contitech.de/fih

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2016 ContiTech AG. All rights reserved. For complete information go to: www.contitech.de/discl\_en

