

Flotide	Dehumidifier(R32)	P2.2/32	P3.5/32	P4.5/32
Part nr		7026879	7026880	7026881
Performance				
Room Condition	Maximum Water Extraction	Wattage	Maximum Water Extraction	Wattage
10°C and 60%°C rh	15.5 liter per day	515	20.5	550
15°C and 60%°C rh	20.8	580	24.3	600
20°C and 60%°C rh	27.5	640	30.3	670
25°C and 60%°C rh	29.5	690	39.2	750
30°C and 60%°C rh	34.1	750	42.1	840
32°C and 60%°C rh	34.6	790	45.3	960
10°C and 80%°C rh	18.5	580	33.5	720
15°C and 80%°C rh	32.1	650	42.3	780
20°C and 80%°C rh	40.5	730	55.1	860
25°C and 80%°C rh	47.5	820	64.5	990
30°C and 80%°C rh	55.6	910	75.3	1120
32°C and 80%°C rh	61.5	1020	80.6	1230
Technical data				
Weight	63 kgs	77 kgs	82 kgs	
Net dimensions	1295x202X647mm	1495x202x647	1695x202x647	
Dimensions (HWD)	1343×248×790mm	1543×248×790mm	1743×248×790mm	
Refrigerant	R32	R32	R32	
Noise level	Maximum 44dB(A) at one metre	Maximum 46dB(A) at one metre	Maximum 48dB(A) at one metre	
Power supply	220-240, 50Hz	220-240, 50Hz	220-240, 50Hz	
Power consumption at 28 and 80%rh	892 watts	1095 watts	1700 watts	
Operating temperatures	10°C - 32°C	10°C - 32°C	10°C - 32°C	
Maximum air flow	450m³/hour	600m³/hour	750m³/hour	
Rated current	4.1 amps	5.1 amps	7.9 amps	
Starting current	4.3 amps	5.85 amps	10 amps	
Rated Capacity	2.2kg	3.5kg	4.5kg	
Relative Humidity	40%-90%	40%-90%	40%-90%	
Condensation Pipe Diameter	7,92	7,92	7,92	