

Lovibond® Water Testing Tintometer® Group



SD40 Multi



- Transparent lid for easy maintenance and storage
- Ideal lid design for a stable stand
- Display colours & symbols for easy use
- New multi-parameter models for individual measurement requirements

Part Number: 720040

Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Municipalities | NGO | Oil and Gas | Pharmaceutical Industry | Pool Public | Pool Services

Application

Boiler Water | Cooling Water | Drinking Water Treatment | Pool Water-Control | Waste Water Treatment

SD40 Multi

With its waterproof housing, the Pocket Tester is ideal for regular checks in industrial plants or swimming pools.

Plus, the transparent lid not only provides a secure stand for the Pocket Tester in daily use, but also makes it easier to maintain the electrodes. A three-colour LED lighting system - blue, green and red - and new display icons make the tester easy to use and intuitive to operate. The use of energy saving LEDs and 4 x AAA batteries greatly extends the life of the new Pocket Tester range to up to 2000 hours.

With the included lanyard, each SD Series tester can be worn comfortably around the neck or attached to a pocket, waistband or belt with the clip on the head of the tester, allowing it to be taken anywhere without tiring the hands.

Measuring Range

Test Name	Measuring Range
Conductivity	0.01 - 20.00 mS/cm
pH	0 - 14
Salinity	0.01 - 10 g/L
TDS	0.01 - 20.00 ppt

Technical Data

Accuracy	pH: ± 0.01 (± 1 digit) pH (mV): ± 0.2 % FS Con/TDS/Salt: ± 1 % FS Temperature: ± 0.5 °C
Display	3 coloured backlit LCD (blue: measurement, green: calibration, red: alarm)
Auto – OFF	Yes
Calibration	1 or 2 points calibration for auto mode Standard: 1413 μ S/cm or Standard: 12.88 mS/cm up to 2 points calibration for manual mode ± 50 % adjustable value
Power Supply	4 micro batteries (AAA)
Battery Life Time	> 2000 h
Portability	Portable
Temperature Compensation	Automatic
Resolution	pH: 0.01; Auto Scale - Con 0.1 μ S/cm, 1 μ S/cm, 0.01 mS/cm; Auto Scale – TDS: 0,1 ppm, 1 ppm, 0.01 ppt; Salt: 0.01 ppt
Resolution Temperature	0.1 °C
Calibration Points	1-3
Buffer Auto Recognition	pH: USA: 1.68 / 4.00 / 7.00 / 10.01 / 12.45 pH NIST: 1.68 / 4.01 / 6.86 / 9.81 / 12.45 pH Con: 84 μ S/cm / 1413 μ S/cm / 12 mS/cm
Calibration Indicator	Yes
Stability Indicator	Yes
Auto-Hold Function	Yes
Alarm Limits	Yes
Environmental Conditions	0 - 60 °C / 0 - 80% rel. humidity (non-condensing)
IP Rating	IP 67

Compliance	CE
Dimensions	40 x 40 x 180 mm
Weight	151 g
Weight with Packaging	268 g

Delivery Scope

- Tester incl. electrode
- 4 batteries
- Lanyard
- Storage box
- pH 4, 7, 10 buffer tablets (1 Strip of 10 tablets each)
- 3 M KCl Storage Solution for pH/ORP
- Multilingual instruction manual
- Certificate of compliance
- Warranty declaration

Title	Part Number
Micro batteries (AAA), set of 4	1950026
Conductivity (1413 µS) and TDS (998 ppm) calibration solution 100 mL	467642
Conductivity (12.89 mS) and TDS (9.02 ppth) calibration solution 100 mL	467643
Replacement electrode for SD40 Multi	720045

Tintometer GmbH

Lovibond® Water Testing
Schleefstraße 8-12
44287 Dortmund
Tel.: +49 (0)231/94510-0
sales@lovibond.com
www.lovibond.com
Germany

The Tintometer Limited

Lovibond House
Sun Rise Way
Amesbury, SP4 7GR
Tel.: +44 (0)1980 664800
sales@lovibond.uk
www.lovibond.com
UK

Tintometer China

9F, SOHO II C. No.9 Guanghualu,
Chaoyang District,
Beijing, 100020
Customer Care Tel.: +86 (021) 69910081
Tel.: +86 10 85251111 Ext. 330
Fax: +86 10 85251001
chinaoffice@tintometer.com
www.lovibond.com
China

Lovibond Tintometer Sdn Bhd

Unit B-3-12, BBT One Boulevard,
Lebuh Batu Nilam 2, Bdr Bkt Tinggi,
41200, Klang, Selangor,
Tel.: +60 (0)3 3325 2285/6
Fax: +60 (0)3 3325 2287
lovibond.asia@tintometer.com
www.lovibond.com
Malaysia

Tintometer Brazil

Caixa Postal: 271
CEP: 13201-970
Jundiaí – SP
Tel.: +55 (11) 3230-6410
sales@lovibond.us
www.lovibond.com.br
Brazil

Tintometer Inc.

6456 Parkland Drive
Sarasota, FL 34243
Tel: 941.756.6410
Fax: 941.727.9654
sales@lovibond.us
www.lovibond.us
USA

Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor
Sanathnagar Industrial Estate,
Hyderabad, 500018
Telangana
Tel: +91 (0) 40 23883300
Toll Free: 1 800 599 3891/ 3892
indiaoffice@lovibond.in
www.lovibondwater.in
India

Tintometer Spain

Postbox: 24047
08080 Barcelona
Tel.: +34 661 606 770
sales@tintometer.es
www.lovibond.com
Spain