

# Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 10

LOCTITE 55 known as Loctite 55

SDS No.: 168432 V005.0 Revision: 06.10.2020 printing date: 04.01.2022 Replaces version from: 06.10.2020

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 55 known as Loctite 55

- **1.2. Relevant identified uses of the substance or mixture and uses advised against** Intended use: Adhesive
- 1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End HP24RQ Hemel Hempstead

Great Britain

Phone:	+44 (1442) 278000
Fax-no.:	+44 (1442) 278071

ua-productsafety.uk@henkel.com

## **1.4. Emergency telephone number**

24 Hours Emergency Tel: +44 (0)1442 278497

# **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

### 2.2. Label elements

## Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

## 2.3. Other hazards

None if used properly. Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

# General chemical description:

Coated Nylon Thread

#### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Contains no dangerous substances exceeding the limits of the EU-Regulation

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation: Move to fresh air, consult doctor if complaint persists.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion: Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

#### 4.2. Most important symptoms and effects, both acute and delayed

Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

#### **4.3. Indication of any immediate medical attention and special treatment needed** See section: Description of first aid measures

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

**Suitable extinguishing media:** carbon dioxide, foam, powder, water spray jet, fine water spray

**Extinguishing media which must not be used for safety reasons:** High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

## 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### Additional information:

In case of fire, keep containers cool with water spray.

## **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures Avoid contact with skin and eyes.Ensure adequate ventilation.Wear protective equipment.

### **6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

## 6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13. Scrape up as much material as possible. Sweep up spilled material. Avoid creating dust. Store in a partly filled, closed container until disposal.

## 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Good industrial hygiene practices should be observed.

## 7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry place. Keep container tightly sealed. Refer to Technical Data Sheet

**7.3.** Specific end use(s) Adhesive

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ррт	mg/m <sup>3</sup>	Value type	Shortterm exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Talc (Mg3H2(SiO3)4) 14807-96-6 [TALC, RESPIRABLE DUST]		1	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUM DIOXIDE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [TITANIUMDIOXIDE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL

## **Occupational Exposure Limits**

Valid for Ireland

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Shortterm exposure limit category/Remarks	Regulatorylist
Limestone		4	Time Weighted Average		IR_OEL
1317-65-3			(TWA):		
[CALCIUM CARBONATE]					
Limestone		10	Time Weighted Average		IR_OEL
1317-65-3			(TWA):		
[CALCIUM CARBONATE]					
Talc (Mg3H2(SiO3)4)		10	Time Weighted Average		IR_OEL
14807-96-6			(TWA):		
[TALC]					
Talc (Mg3H2(SiO3)4)		0,8	Time Weighted Average		IR_OEL
14807-96-6			(TWA):		
[TALC]					
Titanium dioxide		10	Time Weighted Average		IR_OEL
13463-67-7			(TWA):		
[TITANIUM DIOXIDE]					
Titanium dioxide	İ	4	Time Weighted Average		IR_OEL
13463-67-7			(TWA):		
[TITANIUM DIOXIDE]					

#### Biological Exposure Indices: None

#### 8.2. Exposure controls:

Engineering controls: Ensure adequate ventilation.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Flash point

Flammability

Bulk density

Density

Evaporation rate

Explosive limits

Vapour pressure

Relative vapour density:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection: Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance	solid material
	paste
	white
Odor	characteristic
Odour threshold	No data available / Not applicable
рН	Not applicable
Melting point	No data available / Not applicable
Solidification temperature	No data available / Not applicable
Initial boiling point	150 °C (302 °F)

150 °C (302 °F) > 93 °C (>199.4 °F); Closed cup No data available / Not applicable Solubility Solubility (qualitative) (23 °C (73.4 °F); Solvent: Water) Partition coefficient: n-octanol/water Auto-ignition temperature Decomposition temperature Viscosity Viscosity (kinematic) Explosive properties Oxidising properties

#### 9.2. Other information

No data available / Not applicable

No data available / Not applicable Partially soluble

No data available / Not applicable No data available / Not applicable No data available / Not applicable No data available / Not applicable No data available / Not applicable No data available / Not applicable No data available / Not applicable

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

None if used for intended purpose.

## 10.2. Chemical stability

Stable under recommended storage conditions.

## 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

None if used for intended purpose.

**10.5. Incompatible materials** None if used properly.

# 10.6. Hazardous decomposition products

None known.

# SECTION 11: Toxicological information

## General toxicological information:

Prolonged or repeated contact may cause eye irritation. Prolonged or repeated contact may cause skin irritation.

## 11.1. Information on toxicological effects

#### Acute oral toxicity:

No data available.

#### Acute dermal toxicity:

No data available.

#### Acute inhalative toxicity:

No data available.

#### Skin corrosion/irritation:

No data available.

### Serious eye damage/irritation:

No data available.

### Respiratory or skin sensitization:

No data available.

## Germ cell mutagenicity:

No data available.

### Carcinogenicity

No data available.

## **Reproductive toxicity:**

No data available.

## STOT-single exposure:

No data available.

## STOT-repeated exposure::

No data available.

#### Aspiration hazard:

No data available.

## **SECTION 12: Ecological information**

**General ecological information:** Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

### Toxicity (Fish):

No data available.

## Toxicity (Daphnia):

No data available.

#### Chronic toxicity to aquatic invertebrates

No data available.

Toxicity (Algae):

No data available.

#### Toxicity to microorganisms

No data available.

#### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

## 12.4. Mobility in soil

Cured adhesives are immobile.

No substance data available.

### 12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or vPvB.

#### 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations. Do not empty into drains / surface water / ground water.

#### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information		
14.1.	UN number	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.2.	UN proper shipping name	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.3.	Transport hazard class(es)	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.4.	Packing group	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.5.	Environmental hazards	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.6.	S pecial precautions for user	
	Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.	
14.7.	Transport in bulk according to Annex II of Marpol and the IBC Code	
	not applicable	

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture VOC content

(2010/75/EC)

< 3 %

## 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

# SECTION 16: Other information

### **Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

#### Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.