

## Inline RBY Filter

Static filter helps prevent plugging in a drip irrigation system

### Features

- A simple and reliable filter for low-volume irrigation systems
- Simple to clean, as cap has a sealing O-ring and unthreads to provide access to the stainless steel filter element
- Strong and reliable due to its robust design and glass-filled polypropylene construction
- Male x Male threaded connections for direct connection to valves and pressure regulators
- Replacement stainless steel elements are available in 200 mesh (75 micron)

### Operating Range

- Flow:
  - 3/4" units: 0.20 to 12.0 gpm (0.8 to 45.4 l/m)
  - 1" units: 0.20 to 18.0 gpm (0.8 to 68.1 l/m)
- Pressure: 20 to 150 psi (1.4 to 10.3 bar)
- Filtration: 200 mesh (75 micron)

### Models

- RBY075MPTX: 3/4" Inline RBY Filter with 200 Mesh Screen
- RBY100MPTX: 1" Inline RBY Filter with 200 Mesh Screen\*

### Replacement screen:

- RBY-200SSMX (200 mesh stainless steel screen)



RBY075MPTX

### Pressure Loss Characteristics

Flow Rate gpm l/m	RBY075MPTX		RBY100MPTX	
	psi	bar	psi	bar
1.00 0.8	0.1	0.00	0.1	0.00
3.00 3.8	0.4	0.01	0.3	0.01
5.0 11.4	1.1	0.03	0.5	0.02
7.0 18.9	1.6	0.08	0.8	0.03
9.0 26.5	2.7	0.11	1.4	0.06
12.0 34.1	4.5	0.19	2.2	0.10
14.0 45.4	--	0.31	3.0	0.15
16.0 53.0	--	--	3.8	0.21
18.0 60.6	--	--	4.7	0.26
68.1	--	--	--	0.32

Note: Pressure loss for 200 mesh filter screen

## Pressure-Regulating Filter (RBY)

Unique, compact unit that works with all valves to create a simple, efficient control zone. Combines filtration and pressure regulation in one piece for protection of downstream components in a low-volume irrigation system

### Features

- Reduces the number of components in a control zone, making it smaller and easier to install. More control zones can fit in one valve box!
- Combination unit comes with 200 mesh (75 micron) stainless steel reduces the number of connections, making installation easier and faster
- Static RBY filter regulates pressure to a nominal 30 or 40 psi (2.0 or 2.8 bar) -PR RBY Filter Cap has sealing O-ring and unthreads to provide access to the filter element for easy cleaning
- 30 or 40 psi pressure regulator is integrated into the filter body
- Robust body and cap are made of glass-filled polypropylene and provide 150 psi (10.3 bar) pressure rating

### Operating Range

- Flow - 3/4" units: 0.20 to 5.0 gpm (0.8 to 18.9 l/m)
- 1" units: 3.0 to 15.0 gpm (11.4 to 56.8 l/m)
- Inlet pressure: 20 to 150 psi (1.4 to 10.3 bar)
- Regulated pressure: - 3/4" units: 30 psi (2.1 bar)
- 1" units: 40 psi (2.8 bar)

### Models

- PRF-075-RBY: 3/4" PR RBY Filter
- PRF-100-RBY: 1" PR RBY Filter

### Replacement Screen

- RBY-200SSMX (200 mesh stainless steel screen)

Components  
of Control Zone  
Kits Found on  
pg. 147-157

Stainless  
Steel  
Screen



PRF-075-RBY and PRF-100-RBY

### Pressure Loss Characteristics

Flow gpm l/m	PRF-075-RBY		PRF-100-RBY	
	psi	bar	psi	bar
0.2 0.8	3.0	0.21	N/A	N/A
1.0 3.8	4.0	0.28	N/A	N/A
3.0 11.4	6.1	0.42	0.8	0.06
5.0 18.9	10.0	0.69	2.0	0.14
8.0 30.3	N/A	N/A	3.8	0.26
10.0 37.9	N/A	N/A	5.2	0.36
15.0 56.8	N/A	N/A	12.0	0.83

Note: Pressure loss for 200 mesh filter screen