

# PERISTALTIC DOSING PUMP - KBPER



## Features:



<b>TYPE</b>	PE 1.5
<b>POWER SUPPLY</b>	230 Vac 50/60 Hz
<b>CONSUMPTION</b>	8W
<b>TUBING</b>	SANTOPRENE 6,25x10,65mm (I.D.xO.D.)
<b>FLOW ml/REV</b>	2,5
<b>FLOW RATE ml/min</b>	25
<b>FLOW RATE l/h</b>	1,5
<b>FLOW RATE gph</b>	0,398
<b>BACKPRESSURE</b>	1,5 BAR
<b>PUMP BODY MATERIAL</b>	Polypropylene (PP)
<b>PUMP COVER MATERIAL</b>	Polycarbonate (PC)
<b>ROLLERS MATERIAL</b>	Polyoxymethylene (PTFE)
<b>IP DEGREE</b>	IP65
<b>WEIGHT</b>	0,69 Kg (0,97 lb)
<b>DOSING</b>	Fixed flow rate
<b>OPERATING TEMPERATURE</b>	5-50°C
<b>STORAGE TEMPERATURE</b>	-20÷60°C
<b>CERTIFICATION</b>	CE, EAC

## INSTALLATION KIT

<b>FOOT FILTER</b>	Grid filter in PP with ceramic weight
<b>NON RETURN VALVE</b>	FPM Umbrella Non Return Valve
<b>FIXING BRACKET</b>	PC Wall bracket with screw and dowel
<b>SUCTION/DELIVERY TUBING</b>	4x6 PVC (2 m roll)/4x6 PE (2 m roll)
<b>REDUCTION</b>	M 1/2 - F 3/8

## DIMENSION

