PRO-C™

Simple programming and flexible station expansion make Pro-C the professional's choice for residential and light commercial systems.

KEY BENEFITS

- · Number of stations:
 - Modular Pro-C
 - Conventional wiring from 4 to 23 stations
 - Hybrid EZ Decoder option up to 32 total stations (28 stations max. if two-wire only)
 - Fixed PCC with 6- and 12-station options
- 3 independent irrigation programs (4 start times each) allow for customised scheduling
- 1 sensor input available for use with Solar Sync™ or any Clik sensors
- 1P/MV output for pump start relay and master valve activation
- Add a Solar Sync[™] Sensor to save water based on local weather conditions
- Easy Retrieve[™] Memory allows for manual backup and retrieval of preferred settings and programming
- QuickCheck™ Technology provides simple diagnostics of faulty field wiring

OPERATING SPECIFICATIONS

• Transformer input: 120 VAC or 230 VAC

• Transformer output (24 VAC): 1 A

• Station output (24 VAC): 0.56 A

• P/MV output (24 VAC): 0.28 A

· Approvals: IP44 (outdoor), UL, cUL, FCC, CE, RCM, ISED

PRO-C - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

· Warranty period: 2 years



Plastic Indoor Height: 22.9 cm Width: 25.4 cm Depth: 11.4 cm



Plastic Outdoor

Height: 22.9 cm Width: 25.4 cm Depth: 11.4 cm

Model Transformer Indoor/Outdoor Options PC-4 = 4-station base **00** = 120 VAC (blank) = Outdoor model (blank) = No option module controller (internal transformer) **E** = 230 VAC with i = Indoor model PCC-6 = 6-station European connections, **01** = 230 VAC (plug-in transformer) no plug PCC-12 = 12-station **A** = 230 VAC with Australian connections

PC-400 = Modular 4-station outdoor base unit, internal 120 VAC transformer, and plastic cabinet **PCC-601i-E** = Fixed 6-station indoor controller, plug-in 230 VAC transformer with European connections, and plastic cabinet

PCC-1200 = Fixed 12-station outdoor controller, internal 120 VAC transformer, and plastic cabinet

Australian connections (outdoor models have internal transformer with plug) Examples:

Compatible with:

Solar Sync F



ROAM Remote ROAM XL Remote



EZ Decoder System

PC-SERIES STATION EXPANSION Modules Description PCM-300 3-station plug-in module PCM-900 9-station plug-in module PCM-1600 16-station plug-in module PC-DM EZ Decoder output module PCM-1600-KIT Upgrade kit for 16-station plug-in module PC-DM-KIT Upgrade kit for EZ Decoder output module



Smart WaterMark

Recognised as a responsible water-saving tool when used with a Solar Sync Sensor