



Version 1Date of compilation: 26/10/2020Version 5 (replaces version 4)Revision date: 11/12/2023

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: UFI: PROFEC CLEANER A97F-ED88-M12V-J6VU

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against.

SOLVENT CLEANING PRODUCT FOR ADHESIVES AND MATERIALS

Uses advised against:

Uses other than those recommended.

## 1.3 Details of the supplier of the safety data sheet.

Company:	ADHESIVOS KEFREN, S.A.
Address:	Calle del Dolar, Parcela 148. P.I. Las Atalayas. Buzón 20.078
City:	03114 - ALICANTE
Province:	ALICANTE
Telephone:	+34 965116961
Fax:	+34 965116962
E-mail:	kefren@adhesivoskefren.com
Web:	www.adhesivoskefren.com

1.4 Emergency telephone number: +34 965116961 (Only available during office hours; Monday-Friday; 08:00-18:00) UFI: A97F-ED88-M12V-J6VU


## **SECTION 2: HAZARDS IDENTIFICATION.**

## 2.1 Classification of the substance or mixture.


In accordance with Regulation (EC) No 1272/2008: Eye Irrit. 2 : Causes serious eye irritation. Flam. Liq. 2 : Highly flammable liquid and vapour. STOT SE 3 : May cause drowsiness or dizziness.

## 2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008: Pictograms:



# **PROFEC CLEANER**



Version 1	Date of compilation:	26/10/2020
Version 5 (re	places version 4)	<b>Revision date: 11/12/2023</b>

#### Precautionary statements:

, P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/
P370+P378	In case of fire: Use CO2, chemical foam or dusty. Never use water.
P403+P235	Store in a well-ventilated place. Keep cool.

EUH statements: EUH066

Repeated exposure may cause skin dryness or cracking.

Contains: acetone, propan-2-one, propanone butanone, ethyl methyl ketone

### 2.3 Other hazards.

The mixture does not contain substances classified as PBT. The mixture does not contain substances classified as vPvB. The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

## 3.1 Substances.

Not applicable.

## 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008	
Identifiers	Name	Concentrate	Classification	Specifics concentration limits and Acute toxicity estimate
: 606-001-00-8 : 67-64-1 : 200-662-2 : 01-2119471330-49- XXXX	[1] acetone, propan-2-one, propanone	20 - 100 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-
: 606-002-00-3 : 78-93-3 : 201-159-0 : 01-2119457290-43- XXXX	[1] butanone, ethyl methyl ketone	20 - 50 %	Eye Irrit. 2, H319 - Flam. Liq. 2, H225 - STOT SE 3, H336	-

(\*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

[2] Substance with a national workplace exposure limit (see section 8.1).

# **SECTION 4: FIRST AID MEASURES.**

#### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

# **PROFEC CLEANER**



Version 1Date of compilation: 26/10/2020Version 5 (replaces version 4)Revision date: 11/12/2023

#### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

#### Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

#### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

## **SECTION 5: FIREFIGHTING MEASURES.**

The product is Highly inflammable, it can cause or considerably worsen a fire, the necessary prevention measures should be taken and risks avoided. In case of fire, the following measures are recommended:

#### 5.1 Extinguishing media.

### Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

#### 5.2 Special hazards arising from the substance or mixture.

#### Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

#### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

# **PROFEC CLEANER**

Version 1Date of compilation: 26/10/2020Version 5 (replaces version 4)Revision date: 11/12/2023

## SECTION 6: ACCIDENTAL RELEASE MEASURES.

### 6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

#### 6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

#### 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

# SECTION 7: HANDLING AND STORAGE.

## 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use antistatic footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

## 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

		Qualifying quantity (tonnes) for the application of	
Code	Description	Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200

**7.3 Specific end use(s).** Not available.







Version 1Date of compilation: 26/10/2020Version 5 (replaces version 4)Revision date: 11/12/2023

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

## 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m <sup>3</sup>
acatana propan 2 ana propanana	67-64-1	European	Eight hours	500	1210
acetone, propan-2-one, propanone	07-04-1	Union [1]	Short term		
hutanana, athul mathul katana	79 02 2	European	Eight hours	200	600
butanone, ethyl methyl ketone	78-93-3	Union [1]	Short term	300	900

[1] According both Binding Occupational Esposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL). The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:


Name	DNEL/DMEL	Туре	Value
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	1210 (mg/m <sup>3</sup> )
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	200 (mg/m <sup>3</sup> )
acetone, propan-2-one, propanone	DNEL (Workers)	Inhalation, Short term, Local effects	2420 (mg/m <sup>3</sup> )
CAS No: 67-64-1 EC No: 200-662-2	DNEL (Workers)	Dermal, Chronic, Systemic effects	186 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	62 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	62 (mg/kg bw/day)
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	600 (mg/m <sup>3</sup> )
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	106 (mg/m <sup>3</sup> )
butanana, atbud matbud katana	DNEL (Workers)	Dermal, Chronic, Systemic effects	1161 (mg/kg bw/day)
butanone, ethyl methyl ketone CAS No: 78-93-3 EC No: 201-159-0	DNEL (Consumers)	Dermal, Chronic, Systemic effects	412 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	31 (mg/kg bw/day)
	DMEL (Consumers)	Inhalation, Chronic, Systemic effects	106 (mg/m <sup>3</sup> )
	DMEL (Consumers)	Dermal, Chronic, Systemic effects	412 (mg/m3)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated. DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
acetone, propan-2-one, propanone	aqua (freshwater)	10,6 (mg/L)
CAS No: 67-64-1	aqua (marine water)	1,06 (mg/L)

# **PROFEC CLEANER**



# Version 1Date of compilation: 26/10/2020Version 5 (replaces version 4)Revision date: 11/12/2023

EC No: 200-662-2	aqua (intermittent releases)	21 (mg/L)
	STP	100 (mg/L)
	sediment (freshwater)	30,04 (mg/kg
		sediment dw)
	sediment (marine water)	3,04 (mg/kg
		sediment dw)
	soil	29,5 (mg/kg
		soil dw)
	aqua (freshwater)	55,8 (mg/L)
	aqua (marine water)	55,8 (mg/L)
	Soil	22,5 (mg/kg
		soil dw)
	aqua (intermittent releases)	55,8 (mg/L)
butanone, ethyl methyl ketone	STP	709 (mg/L)
CAS No: 78-93-3	sediment (freshwater)	284,74
EC No: 201-159-0		(mg/kg
		sediment dw)
	sediment (marine water)	284,7 (mg/kg
		sediment dw)
	oral (Hazard for predators)	1000 (mg/kg
		food)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

## 8.2 Exposure controls.

## Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %		
Uses:	SOLVENT CLEANING PRODUCT FOR ADHESIVES AND MATERIALS		
<b>Breathing protec</b>	tion:		
PPE:	Filter mask for protection against gases and particles.		
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.		
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:			
Hand protection:			
PPE: Characteristics:	Protective gloves against chemicals. «CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)         Breakthrough time (min.):         > 480         Material thickness (mm):         0,35		
Eye protection:			

# **PROFEC CLEANER**



Version 1Date of compilation: 26/10/2020Version 5 (replaces version 4)Revision date: 11/12/2023

PPE:	Face shield.
Characteristics:	«CE» marking, category II. Face and eye protector against splashing liquid.
CEN standards:	EN 165, EN 166, EN 167, EN 168
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions. Make sure that mobile parts move smoothly.
Observations:	Face shields should offer a field of vision with a dimension in the central line of, at least, 150 mm vertically once attached to the frame.
Skin protection:	
PPE:	Anti-static protective clothing.
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE:	Anti-static safety footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346
Maintenance: Observations:	The footwear should be checked regularly The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

## 9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Colorless

Odour: Organic Solvents

Odour threshold: Not applicable/Not available due to the nature/properties of the product Melting point: Not applicable/Not available due to the nature/properties of the product Freezing point: Not applicable/Not available due to the nature/properties of the product Boiling point or initial boiling point and boiling range: 60 °C

Flammability: Not applicable/Not available due to the nature/properties of the product Lower explosion limit: Not applicable/Not available due to the nature/properties of the product Upper explosion limit: Not applicable/Not available due to the nature/properties of the product Flash point: -15 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product Decomposition temperature: Not applicable/Not available due to the nature/properties of the product pH: Not applicable (Substance/mixture is non-soluble (in water)).

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product Solubility: Not applicable/Not available due to the nature/properties of the product

Hydrosolubility: Not applicable/Not available due to the nature/properties of the product

Liposolubility: Not applicable/Not available due to the nature/properties of the product

Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product Vapour pressure: 200 Pa

Absolute density: Not applicable/Not available due to the nature/properties of the product Relative density: 0.80

Relative vapour density: Not applicable/Not available due to the nature/properties of the product Particle characteristics: Not applicable/Not available due to the nature/properties of the product



Version 1Date of compilation: 26/10/2020Version 5 (replaces version 4)Revision date: 11/12/2023

#### 9.2 Other information

#### Information with regard to physical hazard classes

Flammable liquids:

Sustained combustibility: Yes.

## SECTION 10: STABILITY AND REACTIVITY.

#### 10.1 Reactivity.

The product does not present hazards by their reactivity.

#### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

#### 10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

## 10.4 Conditions to avoid.

Avoid any improper handling.

#### 10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

## 10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

# SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

IRRITANT MIXTURE. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

## 11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

#### Toxicological information about the substances present in the composition.

Name	Acute toxicity			
Name	Туре	Test	Kind	Value
	Oral	LD50	Rat	5800 mg/kg bw [1]
acetone, propan-2-one, propanone		[1] Journal Pg. 609, 19		and Environmental Health. Vol. 15,
	Dermal			
CAS No: 67-64-1 EC No: 200-662-2	Inhalation			

a) acute toxicity;

Not conclusive data for classification.

b) skin corrosion/irritation;

Not conclusive data for classification.

c) serious eye damage/irritation; Product classified:

Eye irritation, Category 2: Causes serious eye irritation.



# **PROFEC CLEANER**

Version 1Date of compilation: 26/10/2020Version 5 (replaces version 4)Revision date: 11/12/2023

d) respiratory or skin sensitisation; Not conclusive data for classification.

e) germ cell mutagenicity; Not conclusive data for classification.

f) carcinogenicity; Not conclusive data for classification.

g) reproductive toxicity; Not conclusive data for classification.

h) STOT-single exposure;
 Product classified:
 Specific target organ toxicity following a single exposure, Category 3: May cause drowsiness or dizziness.

i) STOT-repeated exposure; Not conclusive data for classification.

j) aspiration hazard; Not conclusive data for classification.

# 11.2 Information on other hazards.

## Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health. **Other information** 

There is no information available on other adverse health effects.

# SECTION 12: ECOLOGICAL INFORMATION.

## 12.1 Toxicity.

Name	Ecotoxicity				
Name	Туре	Test	Kind	Value	
	Fish	Toxicity of	Some Common Indu	8300 mg/l (96 h) [1] 1968. A Comparison of the strial Waste Components ed. Prog.Fish-Cult. 30(1):3-8	
acetone, propan-2-one, propanone	Aquatic invertebrates	Ceriodaphn Utilizing the Arch.Enviro and D.M.M Reproductio Comparison Daphnia pu	ia dubia and Daphnia Three-Brood Test. Contam.Toxicol. 20 Adema 1978. Repr on Toxicity Experime of the Sensitivity of Ilex and Daphnia cuc	8450 mg/l (48 h) [1] zzo 1991. The Sensitivity of a magna to Seven Chemicals 0(2):211-217. Canton, J.H., oducibility of Short-Term and nts with Daphnia magna and Daphnia magna with ullata in Short-Term (2):135-140 (Used Reference	
	Aquatic plants	EC50	Algae	7200 mg/l (96 h) [1]	



# **PROFEC CLEANER**

KEFRÊN ADHESIYOS Page 10 of 13 Print date: 11/12/2023

Version 1Date of compilation: 26/10/2020Version 5 (replaces version 4)Revision date: 11/12/2023

CAS No: 67-64-1EC No: 200-662-2[1] Slooff, W. 1982. A Comparative Study on the Short- Term Effects of 15 Chemicals on Fresh Water Organisms Different Tropic Levels. Natl.Tech.Inf.Serv., Springfield, :25 p. (DUT) (ENG ABS) (NTIS/PB83-200386)	ects of 15 Chemicals on Fresh Water Organisms of Tropic Levels. Natl.Tech.Inf.Serv., Springfield, VA
---	---

## 12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present. No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

## 12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation					
Name	Log Pow	BCF	NOECs	Level		
butanone, ethyl methyl ketone	0,29	_	-	Verv low		
CAS No: 78-93-3 EC No: 201-159-0	0,29	-		very low		

## 12.4 Mobility in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

#### 12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

## 12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

## 12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

# SECTION 13: DISPOSAL CONSIDERATIONS.

#### 13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.


Follow the provisions of Directive 2008/98/EC regarding waste management.

# **SECTION 14: TRANSPORT INFORMATION.**

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

**Land:** Transport by road: ADR, Transport by rail: RID. Transport documentation: Consignment note and written instructions **Sea:** Transport by ship: IMDG.





 Version 1
 Date of compilation: 26/10/2020

 Version 5 (replaces version 4)
 Revision date: 11/12/2023

Transport documentation: Bill of lading <u>Air</u>: Transport by plane: ICAO/IATA. Transport document: Airway bill.

#### **14.1 UN number or ID number.** UN No: UN1993

 14.2 UN proper shipping name.

 Description:

 ADR/RID: UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ACETONE PROPAN-2-ONE PROPANONE / BUTANONE ETHYL

 METHYL KETONE), 3, PG II, (D/E)

 IMDG:
 UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ACETONE PROPAN-2-ONE PROPANONE / BUTANONE ETHYL

 METHYL KETONE), 3, PG II (-15°C)

 ICAO/IATA:
 UN 1993, FLAMMABLE LIQUID, N.O.S. (CONTAINS ACETONE PROPAN-2-ONE PROPANONE / BUTANONE ETHYL

 ETHYL METHYL KETONE), 3, PG II

14.3 Transport hazard class(es).

Class(es): 3

**14.4 Packing group.** Packing group: II

# 14.5 Environmental hazards.

Marine pollutant: No Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,<u>S-E</u>

## 14.6 Special precautions for user.

Labels: 3



Hazard number: 33 Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Proceed in accordance with point 6. ADR LQ: 1 L IMDG LQ: 1 L ICAO LQ: 1 L

14.7 Maritime transport in bulk according to IMO instruments.


The product is not transported in bulk.

# SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC) VOC content (p/p): 100 % VOC content: 800 g/l





Version 1Date of compilation: 26/10/2020Version 5 (replaces version 4)Revision date: 11/12/2023

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Kind of pollutant to water (Germany): WGK 1: Slightly hazardous to water. (Autoclassified according to the AwSV Regulations)

#### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## **SECTION 16: OTHER INFORMATION.**

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Classification codes:

Eye Irrit. 2 : Eye irritation, Category 2 Flam. Liq. 2 : Flammable liquid, Category 2 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Changes regarding to the previous version:

- Modification in the values of the physical and chemical properties (SECTION 9).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:Physical hazardsOn basis of test dataHealth hazardsCalculation methodEnvironmental hazardsCalculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Available Product Exposure Scenario.

Abbreviations and acronyms used:

ADR/RID: Agreement concerning the International Carriage of Dangerous Goods by Road.

- AwSV: Facility Regulations for handling substances that are hazardous for the water.
- BCF: Bioconcentration factor.
- CEN: European Committee for Standardization.
- DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
- DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
- EC50: Half maximal effective concentration.
- PPE: Personal protection equipment.
- IATA: International Air Transport Association.
- ICAO: International Civil Aviation Organization.
- IMDG: International Maritime Code for Dangerous Goods.

# **PROFEC CLEANER**



Version 1Date of compilation: 26/10/2020Version 5 (replaces version 4)Revision date: 11/12/2023

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

NOEC: No observed effect concentration.

- PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
- RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

WGK: Water hazard classes.

Key literature references and sources for data: http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation (EU) 2020/878. Regulation (EC) No 1907/2006. Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

# Annex to the extended Safety Data Sheet (eSDS)

# Identification of the substance or mixture

Product definition	: Mono-constituent substance
Code	: 35025
Product name	: ACETONE
Section 1 - Title	
Short title of the exposure scenario	: [200-662-2] Uses in Cleaning Agents - Industrial
List of use descriptors	<ul> <li>Identified use name: Use in cleaning agents - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC09, PROC10, PROC13, PROC19 Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC04 Market sector by type of chemical product: Not applicable. Article category related to subsequent service life: Not applicable.</li> </ul>
Environmental contributing scenarios	: Use in cleaning agents
Health Contributing scenarios	: Use in cleaning agents
Processes and activities covered by the exposure scenario	: Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

# **Section 2 - Exposure controls**

Contributing scenario controlling environmental exposure for 0: Use in cleaning agents				
Product characteristics	:	Substance is a unique structure., Ketone., Readily biodegradable		
Amounts used	:	Annual site tonnage 641		
Frequency and duration of use	:	Emission days 360		
Other conditions affecting environmental exposure	:	Indoor or outdoor use		
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	:	Common practices vary across sites thus conservative process release estimates used.		
Organizational measures to prevent/limit release from site	:	Common practices vary across sites thus conservative process release estimates used.		
Conditions and measures related to external treatment of waste for disposal	:	External treatment and disposal of waste should comply with applicable local and/or national regulations.		
Conditions and measures related to external recovery of waste	:	External treatment and disposal of waste should comply with applicable local and/or national regulations.		

ACETONE	[200-662-2] Uses in Cleaning Agents - Industrial
Contributing scenario contro	olling worker exposure for 0: Use in cleaning agents
Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	: Liquid, vapour pressure > 10 kPa
Frequency and duration of use	: Covers daily exposures up to 8 hours
Other conditions affecting workers exposure	: Assumes a good basic standard of occupational hygiene is implemented
•	Contributing scenarios - Operational conditions and risk management measures
	General exposures (Eye irritation) Use suitable eye protection.
	General exposures (skin Irritant) Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.
	General exposures (closed systems) Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.
	Process sampling Open systems No specific measures identified.
	Mixing operations (open systems) No specific measures identified.
	Spraying/fogging by machine application Ensure material transfers are under containment or extract ventilation.
	Spraying/fogging by machine application Ensure operation is undertaken outdoors.
	Spraying/fogging by machine application Wear a respirator conforming to EN140 with type A/P2 filter or better.
	Bulk transfers Non-dedicated facility No specific measures identified.
	Bulk transfers Dedicated facility No specific measures identified.
	Small package filling No specific measures identified.
	Rolling, Brushing No specific measures identified.
	Equipment cleaning and maintenance No specific measures identified.
	Dipping, immersion and pouring No specific measures identified.
	Hand application - fingerpaints, pastels, adhesives Wear suitable gloves tested to EN374.
Conditions and measures re	lated to personal protection and hygiene

# Section 3 - Exposure estimation and reference to its source

Website:	Not applicable.
Exposure estimation and ref	ence to its source - Environment: 1: Use in cleaning agents
Exposure assessment (environment):	Not available.
EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE	Not available.
Exposure estimation and ref	ence to its source - Workers: 0: Use in cleaning agents
Exposure assessment (human):	Not available.
EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE	Not available.

# Section 4 - GUIDANCE TO DU TO EVALUATE WHETHER HE WORKS INSIDE THE BOUNDARIES SET BY THE ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.			
Health	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.			

# Additional good practice advice beyond the REACH CSA

Environment	:	Not available.
Health	:	Not available.

# Annex to the extended Safety Data Sheet (eSDS)

# Identification of the substance or mixture

: Mono-constituent substance
: 35025
: ACETONE
: [200-662-2] Uses in Cleaning Agents - Professional
<ul> <li>Identified use name: Use in cleaning agents - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC10, PROC11, PROC15, PROC19 Sector of end use: SU22 Subsequent service life relevant for that use: No. Environmental Release Category: ERC08a, ERC08d Market sector by type of chemical product: Not applicable. Article category related to subsequent service life: Not applicable.</li> </ul>
: Use in cleaning agents
: Use in cleaning agents
: Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

# **Section 2 - Exposure controls**

Contributing scenario controlling environmental exposure for 0: Use in cleaning agents				
:	Substance is a unique structure., Ketone., Readily biodegradable			
:	Annual site tonnage 641			
:	Emission days 360			
:	Indoor or outdoor use			
:	Common practices vary across sites thus conservative process release estimates used.			
:	Common practices vary across sites thus conservative process release estimates used.			
:	External treatment and disposal of waste should comply with applicable local and/or national regulations.			
:	External treatment and disposal of waste should comply with applicable local and/or national regulations.			

ACETONE	[200-662-2] Uses in Cleaning Agents - Professional		
Contributing scenario controlling worker exposure for 0: Use in cleaning agents			
Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100% (unless stated differently).		
Physical state	: Liquid, vapour pressure > 10 kPa		
Frequency and duration of use	: Covers daily exposures up to 8 hours		
Other conditions affecting	: Assumes a good basic standard of occupational hygiene is implemented		
workers exposure	Contributing scenarios - Operational conditions and risk management measures		
	General exposures (Eye irritation) Use suitable eye protection.		
	General exposures (skin Irritant) Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.		
	General exposures (closed systems) Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.		
	Process sampling No specific measures identified.		
	Mixing operations (open systems) With local exhaust ventilation Ensure material transfers are under containment or extract ventilation.		
	Mixing operations (open systems) Ensure operation is undertaken outdoors.		
	Mixing operations (open systems) Avoid carrying out activities involving exposure for more than 4 hours.		
	Bulk transfers Non-dedicated facility With local exhaust ventilation Ensure material transfers are under containment or extract ventilation.		
	Bulk transfers Non-dedicated facility Ensure operation is undertaken outdoors.		
	Bulk transfers Non-dedicated facility Avoid carrying out activities involving exposure for more than 4 hours.		
	Bulk transfers Dedicated facility No specific measures identified.		
	Small package filling Dedicated facility No specific measures identified.		
	Equipment cleaning and maintenance Ensure material transfers are under containment or extract ventilation.		
	Equipment cleaning and maintenance Limit the substance content in the product to 25%.		
	Equipment cleaning and maintenance Avoid carrying out operation for more than 4 hours.		
	Spraying or fogging With local exhaust ventilation Ensure material transfers are under containment or extract ventilation.		
	Spraying or fogging Limit the substance content in the product to 25%. Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours.		
	Spraying or fogging		

ACETONE	[200-662-2] Uses in Cleaning Agents - Professional
	Avoid carrying out activities involving exposure for more than 1 hour.
	Spraying or fogging Wear a respirator conforming to EN140 with type A/P2 filter or better.
	Dipping, immersion and pouring
	No specific measures identified.
	Hand application - fingerpaints, pastels, adhesives Limit the substance content in the product to 25%. Wear suitable gloves tested to EN374.
	Hand application - fingerpaints, pastels, adhesives Avoid carrying out operation for more than 1 hour.
Conditions and meas	ures related to personal protection and hygiene

# Section 3 - Exposure estimation and reference to its source

Website:	:	Not applicable.
Exposure estimation and ref	ere	nce to its source - Environment: 1: Use in cleaning agents
Exposure assessment (environment):	:	Not available.
EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE	:	Not available.
Exposure estimation and ref	ere	nce to its source - Workers: 0: Use in cleaning agents
Exposure assessment (human):	:	Not available.
EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE	:	Not available.

# Section 4 - GUIDANCE TO DU TO EVALUATE WHETHER HE WORKS INSIDE THE BOUNDARIES SET BY THE ES

Environment	<ul> <li>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</li> </ul>
Health	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

# Additional good practice advice beyond the REACH CSA

Environment	• Not available.
Health	: Not available.

# Annex to the extended Safety Data Sheet (eSDS)

# Identification of the substance or mixture

:	Mono-constituent substance
:	35025
:	ACETONE
:	[200-662-2] Uses in Coatings - Industrial
:	Identified use name: Use in coatings - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC09, PROC10, PROC13, PROC15, PROC19 Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC04 Market sector by type of chemical product: Not applicable. Article category related to subsequent service life: Not applicable.
:	Coatings
:	Coatings
:	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.
	::

# Section 2 - Exposure controls

Contributing scenario contro	olli	ng environmental exposure for 0: Coatings
Product characteristics	:	Substance is a unique structure., Ketone., Readily biodegradable
Amounts used	:	Annual site tonnage 641
Frequency and duration of use	:	Emission days 360
Other conditions affecting environmental exposure	:	Indoor or outdoor use
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	:	Common practices vary across sites thus conservative process release estimates used.
Organizational measures to prevent/limit release from site	:	Common practices vary across sites thus conservative process release estimates used.
Conditions and measures related to external treatment of waste for disposal	:	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	:	External treatment and disposal of waste should comply with applicable local and/or national regulations.

ACETONE	[200-662-2] Uses in Coatings - Industrial
-	olling worker exposure for 0: Coatings
Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	: Liquid, vapour pressure > 10 kPa
Frequency and duration of use	: Covers daily exposures up to 8 hours
Other conditions affecting workers exposure	: Assumes a good basic standard of occupational hygiene is implemented
	Contributing scenarios - Operational conditions and risk management measures
	General exposures (Eye irritation) Use suitable eye protection.
	General exposures (skin Irritant) Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.
	General exposures (closed systems) Sample via a closed loop or other system to avoid exposure. Handle substance within a closed system.
	Process sampling Open systems No specific measures identified.
	Mixing operations (open systems) No specific measures identified.
	Spraying/fogging by machine application Ensure material transfers are under containment or extract ventilation.
	Spraying/fogging by machine application Ensure operation is undertaken outdoors.
	Spraying/fogging by machine application Wear a respirator conforming to EN140 with type A/P2 filter or better.
	Bulk transfers Non-dedicated facility No specific measures identified.
	Bulk transfers Dedicated facility No specific measures identified.
	Small package filling No specific measures identified.
	Rolling, Brushing No specific measures identified.
	Equipment cleaning and maintenance No specific measures identified.
	Dipping, immersion and pouring No specific measures identified.
	Hand application - fingerpaints, pastels, adhesives Wear suitable gloves tested to EN374.
	Laboratory activities No specific measures identified.
Conditions and measures re	lated to personal protection and hygiene

# Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.
Exposure estimation and ref	erence to its source - Environment: 1: Coatings
Exposure assessment (environment):	: Not available.
EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE	: Not available.
Exposure estimation and ref	erence to its source - Workers: 0: Coatings
Exposure assessment (human):	: Not available.
EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE	: Not available.

# Section 4 - GUIDANCE TO DU TO EVALUATE WHETHER HE WORKS INSIDE THE BOUNDARIES SET BY THE ES

Environment	<ul> <li>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</li> </ul>
Health	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

# Additional good practice advice beyond the REACH CSA

Environment	Not available.	
Health	Not available.	

# Annex to the extended Safety Data Sheet (eSDS)

# Identification of the substance or mixture

Product definition	: Mono-constituent substance
Code	: 35025
Product name	: ACETONE
Section 1 - Title	
Short title of the exposure scenario	: [200-662-2] Uses in Coatings - Professional
List of use descriptors	<ul> <li>Identified use name: Use in coatings - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC10, PROC11, PROC13, PROC15, PROC19 Sector of end use: SU22</li> <li>Subsequent service life relevant for that use: No. Environmental Release Category: ERC08a, ERC08b, ERC08d, ERC08f Market sector by type of chemical product: Not applicable. Article category related to subsequent service life: Not applicable.</li> </ul>
Environmental contributing scenarios	: Use in coatings
Health Contributing scenarios	: Use in coatings
Processes and activities covered by the exposure scenario	: Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

# Section 2 - Exposure controls

Contributing scenario contro	olli	ng environmental exposure for 0: Use in coatings
Product characteristics	:	Substance is a unique structure., Ketone., Readily biodegradable
Amounts used	:	Annual site tonnage 641
Frequency and duration of use	:	Emission days 360
Other conditions affecting environmental exposure	:	Indoor or outdoor use
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	:	Common practices vary across sites thus conservative process release estimates used.
Organizational measures to prevent/limit release from site	:	Common practices vary across sites thus conservative process release estimates used.
Conditions and measures related to external treatment of waste for disposal	:	External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	:	External treatment and disposal of waste should comply with applicable local and/or national regulations.

ACETONE	[200-662-2] Uses in Coatings - Pro	ofessional
Contributing scenario contro	worker exposure for 0: Use in coatings	
Concentration of substance in mixture or article	overs percentage substance in the product up to 100% (unless stated diff	ferently).
Physical state	quid, vapour pressure > 10 kPa	
Frequency and duration of use	overs daily exposures up to 8 hours	
Other conditions affecting workers exposure	ssumes a good basic standard of occupational hygiene is implemented	
	ontributing scenarios - Operational conditions and risk managemen leasures	I <b>t</b>
	eneral exposures (Eye irritation) se suitable eye protection.	
	eneral exposures (skin Irritant) /ear chemical-resistant gloves (tested to EN374) in combination with 'bas mployee training.	ic'
	eneral exposures (closed systems) ample via a closed loop or other system to avoid exposure. Handle substa ithin a closed system.	ance
	rocess sampling o specific measures identified.	
	lixing operations (open systems) With local exhaust ventilation nsure material transfers are under containment or extract ventilation.	
	lixing operations (open systems) nsure operation is undertaken outdoors.	
	lixing operations (open systems) void carrying out activities involving exposure for more than 4 hours.	
	ulk transfers Non-dedicated facility With local exhaust ventilation nsure material transfers are under containment or extract ventilation.	
	ulk transfers Non-dedicated facility nsure operation is undertaken outdoors.	
	ulk transfers Non-dedicated facility void carrying out activities involving exposure for more than 4 hours.	
	ulk transfers Dedicated facility o specific measures identified.	
	mall package filling Dedicated facility o specific measures identified.	
	quipment cleaning and maintenance nsure material transfers are under containment or extract ventilation.	
	quipment cleaning and maintenance mit the substance content in the product to 25%.	
	quipment cleaning and maintenance void carrying out operation for more than 4 hours.	
	praying or fogging With local exhaust ventilation nsure material transfers are under containment or extract ventilation.	
	praying or fogging mit the substance content in the product to 25%. Ensure operation is und utdoors. Avoid carrying out activities involving exposure for more than 4 h	
	praying or fogging	

Date of issue/Date of revision : 09/03/2016

ACETONE	[200-662-2] Uses in Coatings - Professional
	Avoid carrying out activities involving exposure for more than 1 hour.
	Spraying or fogging Wear a respirator conforming to EN140 with type A/P2 filter or better.
	Dipping, immersion and pouring No specific measures identified.
	Laboratory activities No specific measures identified.
	Hand application - fingerpaints, pastels, adhesives Limit the substance content in the product to 25%. Wear suitable gloves tested to EN374.
	Hand application - fingerpaints, pastels, adhesives Avoid carrying out operation for more than 1 hour.
Conditions and meas	ures related to personal protection and hygiene

# Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.
Exposure estimation and ref	erence to its source - Environment: 1: Use in coatings
Exposure assessment (environment):	: Not available.
EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE	: Not available.
Exposure estimation and ref	erence to its source - Workers: 0: Use in coatings
Exposure assessment (human):	: Not available.
EXPOSURE ESTIMATION AND REFERENCE TO ITS SOURCE	: Not available.

# Section 4 - GUIDANCE TO DU TO EVALUATE WHETHER HE WORKS INSIDE THE BOUNDARIES SET BY THE ES

Environment	<ul> <li>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</li> </ul>
Health	<ul> <li>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</li> </ul>

# Additional good practice advice beyond the REACH CSA

Environment	Not available.	
Health	: Not available.	