

## Safety data sheet according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** GRF UNI-100 XT FB 125ML\*30 L1
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Adhesive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Bison International B.V.  
Dr.A.F.Philipsstraat 9  
NL-4462 EW Goes  
PO Box 160  
NL-4460 AD Goes  
tel. +31 88 3235700  
fax. +31 88 3235800  
e-mail: sds@boltonadhesives.com
- **Further information obtainable from:** PSRA
- **1.4 Emergency telephone number:**  
Members of the public seeking specific information on poisons should contact:  
In England and Wales: NHS 111 - dial 111  
In Scotland: NHS 24 - dial 111

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.  
STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

(Contd. on page 2)

GB

## Safety data sheet according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 1)

- **Hazard-determining components of labelling:**

Butanone

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

- **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

- **Labelling of packages where the contents do not exceed 125 ml**

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Butanone

- **Hazard statements**

H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with national regulations.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Determination of endocrine-disrupting properties**

|          |                          |         |
|----------|--------------------------|---------|
| 78-93-3  | Butanone                 | List II |
| 128-37-0 | Butylated hydroxytoluene | List II |

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Adhesive

(Contd. on page 3)

GB

## Safety data sheet according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 2)

**Dangerous components:**

|                                                                                                   |                                                                                    |               |
|---------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|---------------|
| CAS: 78-93-3<br>EINECS: 201-159-0<br>Index number: 606-002-00-3<br>Reg.nr.: 01-2119457290-43-XXXX | Butanone<br>⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319;<br>STOT SE 3, H336, EUH066 | 50-100%       |
| CAS: 128-37-0<br>EINECS: 204-881-4<br>Reg.nr.: 01-2119555270-46-XXXX<br>01-2119565113-46-XXXX     | Butylated hydroxytoluene<br>⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410       | ≥0.025-<0.25% |

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures****General information:** No special measures required.**After inhalation:**Supply fresh air; consult doctor in case of complaints.  
No special measures required.**After skin contact:** Generally the product does not irritate the skin.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** If symptoms persist consult doctor.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media****Suitable extinguishing agents:**Water haze  
Alcohol resistant foam  
Fire-extinguishing powder  
Carbon dioxide**For safety reasons unsuitable extinguishing agents:** Water with full jet**5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

**5.3 Advice for firefighters****Protective equipment:** No special measures required.**Additional information**

Cool endangered receptacles with water spray.

(Contd. on page 4)

GB

## Safety data sheet according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 3)

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Send for recovery or disposal in suitable receptacles.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

#### 78-93-3 Butanone

|     |                                                                                                                   |
|-----|-------------------------------------------------------------------------------------------------------------------|
| WEL | Short-term value: 899 mg/m <sup>3</sup> , 300 ppm<br>Long-term value: 600 mg/m <sup>3</sup> , 200 ppm<br>Sk, BMGV |
|-----|-------------------------------------------------------------------------------------------------------------------|

#### 128-37-0 Butylated hydroxytoluene

|     |                                       |
|-----|---------------------------------------|
| WEL | Long-term value: 10 mg/m <sup>3</sup> |
|-----|---------------------------------------|

(Contd. on page 5)

GB

## Safety data sheet according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 4)

**· DNELs**
**78-93-3 Butanone**

|            |                                           |                       |
|------------|-------------------------------------------|-----------------------|
| Oral       | Consumer, oral, longterm exposition       | 31 mg/kg bw/day       |
| Dermal     | Worker, dermal, longterm exposition       | 1161 mg/kg bw/day     |
|            | Consumer, dermal, longterm exposition     | 412 mg/kg bw/day      |
| Inhalative | Worker, inhalative, shortterm exposition  | 900 mg/m <sup>3</sup> |
|            | Worker, inhalative, longterm exposition   | 600 mg/m <sup>3</sup> |
|            | Consumer DNEL, acute inhalation           | 450 mg/m <sup>3</sup> |
|            | Consumer, inhalative, longterm exposition | 106 mg/m <sup>3</sup> |

**128-37-0 Butylated hydroxytoluene**

|            |                                           |                         |
|------------|-------------------------------------------|-------------------------|
| Oral       | Consumer, oral, longterm exposition       | 0.25 mg/kg bw/day       |
| Dermal     | Worker, dermal, longterm exposition       | 0.5 mg/kg bw/day        |
|            | Consumer, dermal, longterm exposition     | 0.25 mg/kg bw/day       |
| Inhalative | Worker, inhalative, longterm exposition   | 1.76 mg/m <sup>3</sup>  |
|            | Consumer, inhalative, longterm exposition | 0.435 mg/m <sup>3</sup> |

**· PNECs**
**78-93-3 Butanone**

|      |                        |                        |
|------|------------------------|------------------------|
| Oral | Secondary Poisoning    | 1000 mg/kg             |
|      | Fresh water            | 55.8 mg/l              |
|      | Fresh water sediment   | 284.7 mg/kg dry weight |
|      | Marine water           | 55.8 mg/l              |
|      | Marine sediment        | 284.7 mg/kg dry weight |
|      | Soil                   | 22.5 mg/kg             |
|      | Sewage treatment plant | 709 mg/l               |
|      | Sporadic release       | 55.8 mg/l              |

**128-37-0 Butylated hydroxytoluene**

|  |                        |                          |
|--|------------------------|--------------------------|
|  | Fresh water            | 0.000199 mg/l            |
|  | Fresh water sediment   | 0.45819 mg/kg dry weight |
|  | Marine water           | 0.0000199 mg/l           |
|  | Marine sediment        | 0.04582 mg/kg dry weight |
|  | Soil                   | 0.0539 mg/kg             |
|  | Sewage treatment plant | 0.017 mg/l               |

**· Ingredients with biological limit values:**
**78-93-3 Butanone**

|      |                           |
|------|---------------------------|
| BMGV | 70 µmol/L                 |
|      | Medium: urine             |
|      | Sampling time: post shift |
|      | Parameter: butan-2-one    |

**· Additional information:** The lists valid during the making were used as basis.

**· 8.2 Exposure controls**
**· Appropriate engineering controls** No further data; see section 7.

(Contd. on page 6)

GB

## Safety data sheet according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 5)

- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**  
The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.
- **Respiratory protection:**  
Use suitable respiratory protective device in case of insufficient ventilation.
- **Recommended filter device for short term use:** Filter A
- **Hand protection**  
Solvent resistant gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**  
Recommended thickness of the material: > 0,12 mm  
Butyl rubber, BR  
Nitrile rubber, NBR  
Recommended thickness of the material: > 0,7 mm
- **Penetration time of glove material**  
For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).  
For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).
- **Eye/face protection**



Tightly sealed goggles

Goggles recommended during refilling

- **Body protection:** Solvent resistant protective clothing

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Liquid
- **Colour:** According to product specification
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** 79-80.5 °C
- **Flammability** Highly flammable.

(Contd. on page 7)

GB

## Safety data sheet according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 6)

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>· <b>Lower and upper explosion limit</b></li> <li>· <b>Lower:</b></li> <li>· <b>Upper:</b></li> <li>· <b>Flash point:</b></li> <li>· <b>Auto-ignition temperature:</b></li> <li>· <b>Decomposition temperature:</b></li> <li>· <b>pH</b></li> <li>· <b>Viscosity:</b></li> <li>· <b>Kinematic viscosity</b></li> <li>· <b>Dynamic at 20 °C:</b></li> <li>· <b>Solubility</b></li> <li>· <b>water:</b></li> <li>· <b>Partition coefficient n-octanol/water (log value)</b></li> <li>· <b>Vapour pressure at 20 °C:</b></li> <li>· <b>Density and/or relative density</b></li> <li>· <b>Density at 20 °C:</b></li> <li>· <b>Relative density</b></li> <li>· <b>Vapour density</b></li> </ul> | <ul style="list-style-type: none"> <li>1.8 Vol %</li> <li>11.5 Vol %</li> <li>-9 °C</li> <li>514 °C</li> <li>Not determined.</li> <li>Not determined.</li> <li>Not determined.</li> <li>1450 mPas</li> <li>Not miscible or difficult to mix.</li> <li>Not determined.</li> <li>105 hPa</li> <li>0.96-0.962 g/cm<sup>3</sup></li> <li>Not determined.</li> <li>Not determined.</li> </ul>                                                              |
| <ul style="list-style-type: none"> <li>· <b>9.2 Other information</b></li> <li>· <b>Appearance:</b></li> <li>· <b>Form:</b></li> <li>· <b>Important information on protection of health and environment, and on safety.</b></li> <li>· <b>Ignition temperature:</b></li> <li>· <b>Explosive properties:</b></li> <li>· <b>Solvent content:</b></li> <li>· <b>Organic solvents:</b></li> <li>· <b>VOC (EC)</b></li> <li>· <b>Solids content:</b></li> <li>· <b>Change in condition</b></li> <li>· <b>Evaporation rate</b></li> </ul>                                                                                                                                                                                               | <ul style="list-style-type: none"> <li>All relevant physical data were determined for the mixture. All non-determined data are not measurable or not relevant for the characterization of the mixture.</li> <li>Fluid</li> <li>Product is not selfigniting.</li> <li>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</li> <li>77.2 %</li> <li>77.24 %</li> <li>22.7 %</li> <li>Not determined.</li> </ul> |
| <ul style="list-style-type: none"> <li>· <b>Information with regard to physical hazard classes</b></li> <li>· <b>Explosives</b></li> <li>· <b>Flammable gases</b></li> <li>· <b>Aerosols</b></li> <li>· <b>Oxidising gases</b></li> <li>· <b>Gases under pressure</b></li> <li>· <b>Flammable liquids</b></li> <li>· <b>Flammable solids</b></li> <li>· <b>Self-reactive substances and mixtures</b></li> <li>· <b>Pyrophoric liquids</b></li> </ul>                                                                                                                                                                                                                                                                              | <ul style="list-style-type: none"> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Void</li> <li>Highly flammable liquid and vapour.</li> <li>Void</li> <li>Void</li> <li>Void</li> </ul>                                                                                                                                                                                                                                                 |

(Contd. on page 8)

GB

## Safety data sheet according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 7)

|                                                                                    |      |
|------------------------------------------------------------------------------------|------|
| · <b>Pyrophoric solids</b>                                                         | Void |
| · <b>Self-heating substances and mixtures</b>                                      | Void |
| · <b>Substances and mixtures, which emit flammable gases in contact with water</b> | Void |
| · <b>Oxidising liquids</b>                                                         | Void |
| · <b>Oxidising solids</b>                                                          | Void |
| · <b>Organic peroxides</b>                                                         | Void |
| · <b>Corrosive to metals</b>                                                       | Void |
| · <b>Desensitised explosives</b>                                                   | Void |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Danger of forming toxic pyrolysis products.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · **LD/LC50 values relevant for classification:**

##### **78-93-3 Butanone**

|        |      |                   |
|--------|------|-------------------|
| Oral   | LD50 | >2193 mg/kg (rat) |
| Dermal | LD50 | >8050 mg/kg (rat) |

##### **128-37-0 Butylated hydroxytoluene**

|        |      |                   |
|--------|------|-------------------|
| Oral   | LD50 | >2930 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity**  
Not applicable.  
Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 9)

GB

## Safety data sheet according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 8)

- **Additional toxicological information:**
- **Acute effects (acute toxicity, irritation and corrosivity)** Not applicable.
- **Sensitisation** Not applicable.
- **Repeated dose toxicity** Not applicable.
- **11.2 Information on other hazards**

**Endocrine disrupting properties**

|          |                          |         |
|----------|--------------------------|---------|
| 78-93-3  | Butanone                 | List II |
| 128-37-0 | Butylated hydroxytoluene | List II |

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Disposal must be made according to official regulations.
- **Uncleaned packaging:**
- **Recommendation:**  
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

### SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR/ADN, IMDG, IATA** UN1133
- **14.2 UN proper shipping name**
- **ADR/ADN** 1133 ADHESIVES

(Contd. on page 10)

GB

## Safety data sheet

### according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 9)

|                                                                                    |                                                                                                                  |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| · <b>IMDG, IATA</b>                                                                | ADHESIVES                                                                                                        |
| · <b>14.3 Transport hazard class(es)</b>                                           |                                                                                                                  |
| · <b>ADR/ADN</b>                                                                   |                                                                                                                  |
|   |                                                                                                                  |
| · <b>Class</b>                                                                     | 3 (F1) Flammable liquids.                                                                                        |
| · <b>Label</b>                                                                     | 3                                                                                                                |
| · <b>IMDG, IATA</b>                                                                |                                                                                                                  |
|  |                                                                                                                  |
| · <b>Class</b>                                                                     | 3 Flammable liquids.                                                                                             |
| · <b>Label</b>                                                                     | 3                                                                                                                |
| · <b>14.4 Packing group</b>                                                        |                                                                                                                  |
| · <b>ADR/ADN, IMDG, IATA</b>                                                       | III                                                                                                              |
| · <b>14.5 Environmental hazards:</b>                                               |                                                                                                                  |
| · <b>Marine pollutant:</b>                                                         | No                                                                                                               |
| · <b>14.6 Special precautions for user</b>                                         | Warning: Flammable liquids.                                                                                      |
| · <b>Hazard identification number (Kemler code):</b>                               | -                                                                                                                |
| · <b>EMS Number:</b>                                                               | F-E,S-D                                                                                                          |
| · <b>Stowage Category</b>                                                          | A                                                                                                                |
| · <b>14.7 Maritime transport in bulk according to IMO instruments</b>              | Not applicable.                                                                                                  |
| · <b>Transport/Additional information:</b>                                         |                                                                                                                  |
| · <b>Quantity limitations</b>                                                      | On passenger aircraft/rail: 60 L<br>On cargo aircraft only: 220 L                                                |
| · <b>ADR/ADN</b>                                                                   |                                                                                                                  |
| · <b>Limited quantities (LQ)</b>                                                   | 5L                                                                                                               |
| · <b>Excepted quantities (EQ)</b>                                                  | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>Transport category</b>                                                        | 3                                                                                                                |
| · <b>Tunnel restriction code</b>                                                   | E                                                                                                                |
| · <b>IMDG</b>                                                                      |                                                                                                                  |
| · <b>Limited quantities (LQ)</b>                                                   | 5L                                                                                                               |

(Contd. on page 11)

GB

## Safety data sheet according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 10)

|                                   |                                                                                                                                                                                               |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| · <b>Excepted quantities (EQ)</b> | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml                                                                              |
| · <b>Remarks:</b>                 | For substances with class 3 according to IMDG-Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time $t > 100$ s). |
| · <b>UN "Model Regulation":</b>   | UN 1133 ADHESIVES, 3, III                                                                                                                                                                     |

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

#### · **Regulated explosives precursors**

None of the ingredients is listed.

#### · **Regulated poisons**

None of the ingredients is listed.

#### · **Reportable explosives precursors**

None of the ingredients is listed.

#### · **Reportable poisons**

None of the ingredients is listed.

#### · **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

#### · **Seveso category P5c FLAMMABLE LIQUIDS**

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

#### · **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

#### · **REGULATION (EU) 2019/1148**

#### · **Regulation (EC) No 273/2004 on drug precursors**

78-93-3 Butanone

3

#### · **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

78-93-3 Butanone

3

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 12)

## Safety data sheet according to UK REACH

Printing date 31.07.2025

Version number 35 (replaces version 34)

Revision: 31.07.2025

**Trade name:** GRF UNI-100 XT FB 125ML\*30 L1

(Contd. of page 11)

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

#### · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

|                                                                                   |                                                                                                                                                |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Flammable liquids                                                                 | Bridging principles                                                                                                                            |
| Serious eye damage/irritation<br>Specific target organ toxicity (single exposure) | The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. |

#### · Department issuing SDS: PSRA

#### · Contact: PSRA

#### · Date of previous version: 24.06.2025

#### · Version number of previous version: 34

#### · Abbreviations and acronyms:

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (UK REACH)
- PNEC: Predicted No-Effect Concentration (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

#### · \* Data compared to the previous version altered.

GB