

Qty.	Description
1	<p>SQE 2-85 Product No.: On request 3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing.</p> <p>The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature.</p> <p>The motor is a single-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range. The motor is fitted with a replaceable end cover with socket.</p> <p>Liquid: Pumped liquid: Water Liquid temperature range: 0 .. 35 °C Selected liquid temperature: 20 °C Density: 998.2 kg/m³</p> <p>Technical: Pump speed on which pump data are based: 10700 rpm Rated flow: 2 m³/h Rated head: 88 m Approvals: CE,PCBC,RCM,EAC,CN Rohs Exempt,Morocco,UKCA,SEPRO Curve tolerance: ISO9906:2012 3B</p> <p>Materials: Pump: Stainless steel EN 1.4301 AISI 304 Impeller: Composite ZYTEL 70G30 HSLR PA6.6-GF30 Motor: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation: Maximum operating pressure: 15 bar Pump outlet: RP1 1/4 Minimum borehole diameter: 76 mm</p> <p>Electrical data: Motor type: MSE3 Power input - P1: 1.55 kW Rated power - P2: 1.15 kW Power (P2) required by pump: 1.13 kW Mains frequency: 50 Hz Rated voltage: 1 x 200-240 V Rated current: 8.4 A Power factor: 1.00</p>



Company name:

Created by:

Phone:


Date:

19/05/2026


Qty.	Description
------	-------------

1	Rated speed: 10700 rpm
	Start. method: direct-on-line
	Enclosure class (IEC 34-5): IP68
	Insulation class (IEC 85): F
	Length of cable: 1.5 m
	Motor No: 96160855
	Others:
	Net weight: 5.14 kg
	Gross weight: 5.86 kg
	Shipping volume: 0.01 m ³
	Danish VVS No.: 388442485
	Swedish RSK No.: 5853372
	Finnish LVI No.: 4762532
	Norwegian NRF no.: 9041353



On request SQE 2-85 50 Hz



Description	Value
General information:	
Product name:	SQE 2-85
Product No:	On request
EAN number:	On request
Technical:	
Pump speed on which pump data are based:	10700 rpm
Rated flow:	2 m ³ /h
Rated head:	88 m
Stages:	5
Approvals:	CE,PCBC,RCM,EAC,CN Rohs Exempt,Morocco,UKCA,SEPRO
Curve tolerance:	ISO9906:2012 3B
Pump No:	96080395
Model:	C
Valve:	pump with built-in non-return valve
Materials:	
Pump:	Stainless steel EN 1.4301 AISI 304
Impeller:	Composite ZYTEL 70G30 HSLR PA6.6-GF30
Motor:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Installation:	
Maximum operating pressure:	15 bar
Pump outlet:	RP1 1/4
Minimum borehole diameter:	76 mm
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 35 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m ³
Electrical data:	
Motor type:	MSE3
Power input - P1:	1.55 kW
Rated power - P2:	1.15 kW
Power (P2) required by pump:	1.13 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 200-240 V
Rated current:	8.4 A
Power factor:	1.00
Rated speed:	10700 rpm
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Built-in motor protection:	Y
Thermal protec:	internal
Length of cable:	1.5 m
Motor No:	96160855
Controls:	
CU 300/CU 301:	communication with CU 300/CU 301 possible
Others:	
Net weight:	5.14 kg



Pumped liquid = Water
Liquid temperature during operation = 20 °C
Density = 998.2 kg/m³





Company name:

Created by:


Phone:

Date:

19/05/2026


Description	Value
Gross weight:	5.86 kg
Shipping volume:	0.01 m ³
Sales region:	EU/S-AMREG/APREG
Danish VVS No.:	388442485
Swedish RSK No.:	5853372
Finnish LVI No.:	4762532
Norwegian NRF no.:	9041353

On request SQE 2-85 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

On request SQE 2-85 50 Hz



Note! All units are in [mm] unless others are stated.

