

PRO-SPRAY™

Meet the strongest, most versatile spray sprinkler body in the industry.

KEY BENEFITS

- Industry's strongest spray body for years of reliable performance
- Co-moulded wiper seal made from chemical- and chlorine-resistant materials
- Innovative seal design prevents cap-to-body leaks
- Heavy-duty spring for consistent riser retraction
- Check valve option eliminates low-head drainage

ADDITIONAL FEATURES

- Directional flush plug design for cleaner installation
- Interchangeable components for easier servicing, retrofits, and upgrades

OPERATING SPECIFICATIONS

- Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa
- SASO Quality Mark Certified
- Warranty period: 5 years

FACTORY-INSTALLED OPTIONS

- Check valve available for 10 cm, 15 cm, and 30 cm models (up to 3 m of elevation)
- Reclaimed water ID cap

USER-INSTALLED OPTIONS

- Drain check valve (up to 3 m of elevation; P/N 437400SP)
- Reclaimed water ID cap (P/N 458520SP)
- Snap-on reclaimed cover (P/N PROS-RC-CAP-SP)
- Shutoff cap (P/N 213600SP)
- Shutoff nozzle (P/N 916400SP)



Pro-Spray Reclaimed

Pro-Spray models include optional factory-installed purple reclaimed caps.

PRO-SPRAY - SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Options
PROS-00 = Shrub adapter	(blank) = No option
PROS-02 = 5 cm pop-up	CV = Factory-installed drain check valve (Pop-up models only)
PROS-03 = 7.5 cm pop-up	R = Factory-installed reclaimed body cap (shrub moulded in purple)
PROS-04 = 10 cm pop-up	
PROS-06 = 15 cm pop-up (no side inlet)	
PROS-12 = 30 cm pop-up (no side inlet)	

PRO-SPRAY (SIDE INLET) MODELS

PROS-06-SI = 15 cm pop-up with side inlet

PROS-12-SI = 30 cm pop-up with side inlet

Examples:

PROS-06-CV = 15 cm pop-up, drain check valve

PROS-12-CV-R = 30 cm pop-up, drain check valve, reclaimed body cap



PROS-00

Retracted height: 4 cm
Inlet size: ½"



PROS-02

Retracted height: 10 cm
Pop-up height: 5 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



PROS-03

Retracted height: 12.5 cm
Pop-up height: 7.5 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



PROS-04

Retracted height: 15.5 cm
Pop-up height: 10 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



[A] PROS-06-SI

[B] PROS-06
Retracted height: 22.5 cm
Pop-up height: 15 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



[A] PROS-12-SI

[B] PROS-12
Retracted height: 41 cm
Pop-up height: 30 cm
Exposed diameter: 5.7 cm
Inlet size: ½"

PRO-SPRAY™ PRS30

To maintain consistent performance and reduce water waste, the Pro-Spray PRS30 Sprinkler Body is pressure-regulated to an optimal pressure of 2.1 bar; 210 kPa.

KEY BENEFITS

- Industry's strongest sprinkler body for years of reliable performance
- Pressure-regulated to 2.1 bar; 210 kPa for optimal nozzle performance
- Brown cap for easy field identification
- Co-moulded wiper seal made from chemical- and chlorine-resistant materials
- Innovative seal design prevents cap-to-body leaks, even with a loose cap
- FloGuard™ Technology option eliminates water waste in the event of a missing nozzle

ADDITIONAL FEATURES

- Directional flush plug design for cleaner installation
- Interchangeable components for easier servicing, retrofits, and upgrades
- Heavy-duty spring for consistent riser retraction
- Check valve option eliminates low-head drainage

OPERATING SPECIFICATIONS

- Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa
- *SASO Quality Mark Certified
- Warranty period: 5 years

FACTORY-INSTALLED OPTIONS

- Check valve available for 10 cm, 15 cm, and 30 cm models (up to 4.3 m of elevation)
- Reclaimed water identification
- FloGuard Technology available for check valve models

USER-INSTALLED OPTIONS

- Check valve: P/N 437400SP
 - Up to 3 m of elevation for 7.5 cm model
 - Up to 4.3 m of elevation for 10 cm, 15 cm, and 30 cm models
- Reclaimed water ID cap: P/N 458560SP
- Snap-on reclaimed cover: P/N PROS-RC-CAP-SP
- Shutoff cap: P/N 213600SP
- Shutoff nozzle: P/N 916400SP



PRS30 Reclaimed

PRS30 models include optional factory-installed purple reclaimed caps



FloGuard Technology

Eliminate water waste in the event of a missing nozzle



Smart WaterMark

Recognised as a responsible water-saving tool



PROS-00-PRS30*

Retracted height: 11 cm
Inlet size: ½"



PROS-03-PRS30

Retracted height: 12.5 cm
Pop-up height: 7.5 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



PROS-04-PRS30*

Retracted height: 15.5 cm
Pop-up height: 10 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



[A] PROS-06-SI-PRS30*

[B] PROS-06-PRS30*
Retracted height: 22.5 cm
Pop-up height: 15 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



[A] PROS-12-SI-PRS30*

[B] PROS-12-PRS30*
Retracted height: 41 cm
Pop-up height: 30 cm
Exposed diameter: 5.7 cm
Inlet size: ½"

PRO-SPRAY PRS30 – SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Feature Options	3 Specialty Options
PROS-00-PRS30 = 2.1 bar regulated shrub adapter PROS-03-PRS30 = 2.1 bar regulated 7.5 cm pop-up PROS-04-PRS30 = 2.1 bar regulated 10 cm pop-up PROS-06-PRS30 = 2.1 bar regulated 15 cm pop-up PROS-12-PRS30 = 2.1 bar regulated 30 cm pop-up	(blank) = No option CV = Factory-installed drain check valve <i>(10 cm, 15 cm, 30 cm models only)</i>	(blank) = No option R = Factory-installed reclaimed body cap F = FloGuard Technology <i>(10 cm, 15 cm, 30 cm models only)</i> F-R = FloGuard Technology with reclaimed body cap <i>(10 cm, 15 cm, 30 cm models only)</i>

PRO-SPRAY PRS30 (SIDE INLET) MODELS

PROS-06-SI-PRS30 = 2.1 bar regulated 15 cm pop-up with side inlet

PROS-12-SI-PRS30 = 2.1 bar regulated 30 cm pop-up with side inlet

Examples:

PROS-06-SI-PRS30 = 15 cm pop-up with side inlet regulated at 2.1 bar; 210 kPa
PROS-06-PRS30-CV = 15 cm pop-up regulated at 2.1 bar; 210 kPa, drain check valve
PROS-12-PRS30-CV-F-R = 30 cm pop-up regulated at 2.1 bar; 210 kPa, drain check valve, and FloGuard Technology with reclaimed body cap

Compatible with:



Pro Adjustable Nozzles
Page 78

Pro Fixed Nozzles
Page 82

Pro High-Efficiency Nozzles
Page 76

PRO-SPRAY™ PRS40

To optimise MP Rotator™ Nozzle performance, the Pro-Spray PRS40 Sprinkler Body is pressure-regulated to 2.8 bar; 280 kPa.

KEY BENEFITS

- Industry's strongest sprinkler body for years of reliable performance
- Pressure-regulated to 2.8 bar; 280 kPa for the MP Rotator Nozzle
- Grey cap for easy field identification
- Co-moulded wiper seal made from chemical- and chlorine-resistant materials
- Innovative seal design prevents cap-to-body leaks, even with a loose cap
- FloGuard™ Technology option eliminates water waste in the event of a missing nozzle

ADDITIONAL FEATURES

- Directional flush plug design for cleaner installation
- Interchangeable components for easier servicing, retrofits, and upgrades
- Heavy-duty spring for consistent riser retraction
- Check valve option eliminates low-head drainage

OPERATING SPECIFICATIONS

- Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa
- *SASO Quality Mark Certified
- Warranty period: 5 years

FACTORY-INSTALLED OPTIONS

- Check valve available for 10 cm, 15 cm, and 30 cm models (up to 4.3 m of elevation)
- Reclaimed water identification
- FloGuard Technology available for pop-up models

USER-INSTALLED OPTIONS

- Check valve: P/N 437400SP
 - Up to 3 m of elevation for 7.5 cm model
 - Up to 4.3 m of elevation for 10 cm, 15 cm, and 30 cm models
- Reclaimed water ID cap: P/N 458562SP
- Snap-on reclaimed cover: P/N PROS-RC-CAP-SP
- Shutoff cap: P/N 213600SP
- Shutoff nozzle: P/N 916400SP



PRS40 Reclaimed

PRS40 models include optional factory-installed purple reclaimed caps



FloGuard Technology

Eliminate water waste in the event of a missing nozzle



Smart WaterMark

Recognised as a responsible water-saving tool



PROS-00-PRS40*

Retracted height: 11 cm
Inlet size: ½"



PROS-03-PRS40

Retracted height: 12.5 cm
Pop-up height: 7.5 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



PROS-04-PRS40-CV*

Retracted height: 15.5 cm
Pop-up height: 10 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



PROS-06-PRS40-CV*

Retracted height: 22.5 cm
Pop-up height: 15 cm
Exposed diameter: 5.7 cm
Inlet size: ½"



PROS-12-PRS40-CV*

Retracted height: 41 cm
Pop-up height: 30 cm
Exposed diameter: 5.7 cm
Inlet size: ½"

PRO-SPRAY PRS40 – SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Feature Options	3 Specialty Options
PROS-00-PRS40 = 2.8 bar regulated shrub adapter PROS-03-PRS40 = 2.8 bar regulated 7.5 cm pop-up PROS-04-PRS40 = 2.8 bar regulated 10 cm pop-up PROS-06-PRS40 = 2.8 bar regulated 15 cm pop-up PROS-12-PRS40 = 2.8 bar regulated 30 cm pop-up	(blank) = No option CV = Factory-installed drain check valve <i>(10 cm, 15 cm, 30 cm models only)</i>	(blank) = No option R = Factory-installed reclaimed body cap F = FloGuard Technology <i>(10 cm, 15 cm, 30 cm models only)</i> F-R = FloGuard Technology with reclaimed body cap <i>(10 cm, 15 cm, 30 cm models only)</i>

PRO-SPRAY PRS40 (SIDE INLET) MODELS

PROS-06-SI-PRS40 = 2.8 bar regulated 15 cm pop-up with side inlet

PROS-12-SI-PRS40 = 2.8 bar regulated 30 cm pop-up with side inlet

Examples:

PROS-06-SI-PRS40 = 15 cm pop-up with side inlet regulated at 2.8 bar; 280 kPa

PROS-06-PRS40-CV = 15 cm pop-up regulated at 2.8 bar; 280 kPa, drain check valve

PROS-12-PRS40-CV-F-R = 30 cm pop-up regulated at 2.8 bar; 280 kPa, drain check valve, and FloGuard Technology with reclaimed body cap

Compatible with:



MP Rotator Nozzles
Page 54