

Technical Data							
Item nr		7047594/7047602		7047595/7047603			
Advised pool volume(m3)	35~50	50~70	65~90	80~120	100~140	130~190	160~220
Production at 125% (g/h, Recommend salt level)	10	15	20	25	30	40	50
Production at 125% (g/h, Lowest salt level)	8	12	16	20	24	32	40
Production at 100% (g/h, Lowest salt level)	8	12	16	20	18	24	30
Technical Specification							
Salinity Operating range(g/L)	0.6~5						
Recommend Salinity Operating range(g/L)	0.6~2.5 (Recommend 1.5)				2.5~5.0 (Recommend 3.6)		
Power Supply	220-240V~ 50/60Hz						
Max power input(W)	204	204	324	324	204	324	324
Operation AT temp(°C)	-10~45						
Operation WT temp(°C)	5~43						
Water Flow Volume (m3/h)	5~28						
Recommend Water Pressure (Bar)	3						
Water connection (mm)	48.3 / 50						
Cell life time(h)	12000						
Configuration							
Sanility detection	Yes						
Display	7-inch Capacitive Touch Colorful Display						
Operation mode	Boost/Auto/AI/Pool cover/Winter/Timer						
Communications	RS485/Dry contact						
Self cleaning	Yes(adjustable 2~8h)						
Device control	Filtration pump/Back wash/Pool Light/UV/Heat pump max to 8 devices						
Languages	14 languages						
Package							
Net weight(kg)	10			11			
Package Weight(kg)	11			12			
Package dimension L*W*H(mm)	600*400*350						