

# Lovibond® Water Testing Tintometer® Group



## MD150 Chlorine, pH, tablet reagents

Your daily companion for water analysis



The MD150 has several key features that make it a favourite among users.

### – Multiparameter combinations

The MD150 provides essential parameters for pool water monitoring and disinfection control, including Chlorine, Bromine, Ozone, Chlorine Dioxide, pH, Cyanuric Acid, Alkalinity, and Calcium Hardness.

### – Factory programmed methods

The MD150 comes with pre-programmed methods for pool and various other applications, ready to use out of the box.

### – Flexible reagent options: compatible with tablets, powder or liquid

Compatible with various reagent types, simply select your preferred reagent in the settings, and the method list will display only the relevant options.

### – Built for durability

The MD150 features a durable design with rubber-protected sides ensuring reliability even in demanding environments. With its IP67 rating, the instrument offers full protection against dust and water immersion.

### – Ergonomic design

The MD150 is a compact, handheld instrument ideal for the use of the poolside, in the field, or in the lab. Its compact size and side protections ensure a firm grip, while rubber feet prevent slipping, enabling for single-handed operation.

### – Quick and accurate results

The innovative optical system of the MD150 provides exceptional accuracy and fast results, delivering precise measurements in record time.

### – One-Time-Zero function

Save operation time with the One-Time-Zero function, which remains valid for 8 hours unless the instrument is turned off

### – Data transfer – NFC / USB-C

- Wireless (NFC) and wired (USB-C) data transfer options
- Free Software and App for easy data management
- Intuitive user interface with easy-use icons and animations
- Exceptional durability to withstand demanding conditions

Part Number: 282100

Easily transfer data wirelessly via NFC to the AquaLX® app or via USB-C cable to Lovibond® Data Expert. Data can be exported in CSV format for use in programs like Excel.

### – GLP (Good Laboratory Practice) compliance

The MD150 automatically records and saves a protocol for every change, ensuring data quality and integrity by tracking any adjustments that could impact measurement results.

### – Automatic data storage

The MD150 automatically stores the last 100 readings and protocols with a time/date stamp and retains the data even during battery changes.

### – Keep your instrument up to date

Easily update the firmware and methods in seconds using Lovibond® Data Expert. Updates are available on the instrument's webpage.

### – User defined method

With the free of charge Lovibond® Data Expert, you can create custom methods.

## Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Marine Industry | Municipalities | NGO | Oil and Gas | Pharmaceutical Industry | Pool Domestic | Pool Public | Pool Services | Power and Energy

## Application

Boiler Water | Cooling Water | Disinfection Control | Drinking Water Treatment | Pool Water Control | Raw Water Treatment | Waste-Water Treatment

## MD150 Chlorine, pH, tablet reagents

The MD150, building on the legacy of the proven MD100 photometer, offers even more high-quality features and ease of use. Whether you're monitoring pool water or managing other water treatment needs, the MD150 provides versatile multiparameter combinations. With enhanced high-precision optics, the MD150 delivers unmatched accuracy and efficiency, making it the ideal solution for various water testing needs.

## Measuring Range

Test Name	Measuring Range	Chemical Method
Chlorine HR 2 PP	0.1 - 10 mg/L Cl <sub>2</sub>	DPD
Chlorine HR T	0.1 - 10 mg/L Cl <sub>2</sub> <sup>a)</sup>	DPD
Chlorine L	0.02 - 4.0 mg/L Cl <sub>2</sub> <sup>a)</sup>	DPD
Chlorine PP	0.02 - 2 mg/L Cl <sub>2</sub> <sup>a)</sup>	DPD
Chlorine T	0.02 - 6.0 mg/L Cl <sub>2</sub> <sup>a)</sup>	DPD
pH value L	6.5 - 8.4 pH	Phenol Red
pH-value T	6.5 - 8.4 pH	Phenol Red

## Technical Data

<b>Optics</b>	LED, spectrometer sensor, interference filter (only MD50 selected variants)
<b>Light Source</b>	LED
<b>Wavelength</b>	Variant specific (415, 445, 480, 515, 530, 555, 590, 630, 680)
<b>Photometric Range</b>	0 - 3 Abs
<b>Photometric Accuracy</b>	3 % FS (T = 20 °C – 25 °C)
<b>Suitable Vials</b>	Round Cuvettes 13 mm Round Cuvettes 16 mm Round Cuvettes 24 mm
<b>Display</b>	Backlit LCD
<b>Interfaces</b>	USB-C NFC (Near Field Communication)
<b>Data Transfer Format</b>	.csv
<b>Operation</b>	Foil keypad
<b>Auto – OFF</b>	Yes
<b>Programmability</b>	yes with Lovibond Data Expert software
<b>Calibration</b>	Factory and user adjustment - return to factory adjustment possible at any time
<b>Updates</b>	Firmware and methods update
<b>Internal Storage</b>	Internal ring memory for 100 data records
<b>Power Supply</b>	2 x AA batteries Alkaline Batteries (LR6) 3V DC / 55mA
<b>Battery Life Time</b>	approx. 5000 measurements (without backlight)
<b>Portability</b>	Portable
<b>Degree of Pollution</b>	2
<b>Maximum altitude above sea level</b>	3500 m
<b>Environmental Conditions</b>	5 - 50 °C at a relative humidity of 30 - 95 % (non-condensing)
<b>IP Rating</b>	IP 67

<b>Compliance</b>	CE
<b>Languages Full User Manual</b>	English, German, Spanish, French, Portuguese, Italian, Dutch, Turkish, Chinese
<b>Dimensions</b>	155 x 76 x 45 mm
<b>Weight</b>	247 g

## Delivery Scope

- 1 Instrument in Carrying case
- 100 tablet reagents DPD No.1
- 100 tablet reagents DPD No.3 Evo
- 100 tablet reagents Phenol Red Photometer
- 2 batteries (AA)
- 3 round cuvettes (glass) with lid and Sealing rings
- 1 Screwdriver
- 3 Stirring rods
- 1 Syringe 10 mL
- 1 Cleaning brush
- 1 USB-C to USB-A cable
- 1 Instruction manual
- 1 Certificate (COC)
- 1 Warranty information

Title	Part Number
Water Sampler & 250 mL Bottle	170500
Round cuvette 24 mm ø, set of 12	197620
Sealing ring for round vials 24 mm ø, set of 12	197626
Round cuvette 24 mm ø, set of 5	197629
Cleaning cloth	197635
USB-C cable 1 m, USB-C to A	19820-081
Verification Standard Kit MD50/MD150	215700
Reference Standard Kit Chlorine - 0.2 and 1.0 mg/l (MD150)	275630
Reference Standard Kit Chlorine - 0.5 and 2.0 mg/l (MD150)	275631
Reference Standard Kit Chlorine - 1.0 and 4.0 mg/l (MD150)	275632
Reference Standard Kit pH - 7.45 (MD 150)	275635
Stirring rod, 13 cm length	364100
Stirring rod, 10 cm length	364109
Box with 10 plastic stirring rods	364120
Box with 10 plastic stirring rods	364130
250 mL bottle with cap	375072
Brush, 11 cm length	380230
Measuring beaker, 100 ml	384801
Cuvette stand for 6 round cuvettes Ø 24 mm	418951
Plastic funnel with handle (white)	471007
ValidCheck Chlorine 1,5 mg/l	48105510

---

**Tintometer GmbH**

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
sales@lovibond.com  
www.lovibond.com  
Germany

**The Tintometer Limited**

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
sales@lovibond.uk  
www.lovibond.com  
UK

**Tintometer China**

9F, SOHO II C. No.9 Guanghualu,  
Chaoyang District,  
Beijing, 100020  
Customer Care Tel.: +86 (021) 69910081  
Tel.: +86 10 85251111 Ext. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

**Lovibond Tintometer Sdn Bhd**

Unit B-3-12, BBT One Boulevard,  
Lebuh Batu Nilam 2, Bdr Bkt Tinggi,  
41200, Klang, Selangor,  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malaysia

**Tintometer Brazil**

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@lovibond.us  
www.lovibond.com.br  
Brazil

**Tintometer Inc.**

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.us  
USA

**Tintometer India Pvt. Ltd.**

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
India

**Tintometer Spain**

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Spain