

Flotile	Model	PX7/32	PX11/32	PX14/32	PX17/32	PX21/32	PX25/32	PX25T/32	PX30/32	PX30T/32	
Part nr.		7028283	7028284	7028285	7028286	7028287	7028288	7028289	7028290	7028291	
Heating capacity A27/W27 (max.-min.)	kW	7.24-1.82	11-2.23	14-2.52	16-3.25	19-3.5	25.5-5.7	25.5-5.7	30-6.7	30-6.7	
Heating capacity A15/W25 (max.-min.)	kW	5.64-1.39	7.9-1.58	9.5-1.79	12.6-2.55	14-2.55	18.6-4.68	18.6-4.68	23.7-5.46	23.7-5.46	
Heating capacity A0/W25 (max.-min.)	kW	3.91-0.96	5.48-1.10	6.59-1.24	8.74-1.77	9.71-1.77	12.9-3.25	12.9-3.25	16.44-3.79	16.44-3.79	
Heating capacity A-5/W25 (max.-min.)	kW	3.21-0.79	4.50-0.90	5.41-1.02	7.17-1.45	7.97-1.45	10.59-2.66	10.59-2.66	13.5-3.11	13.5-3.11	
Power input (max.-min.)	kW	1.8-0.13	2.05-0.15	2.15-0.16	3.7-0.22	3.8-0.25	5.24-0.35	6.78-0.35	7.22-0.42	7.35-0.42	
Swimming pool volume*	m ³	20-35	30-53	40-70	45-79	55-96	75-131	75-131	100-175	100-175	
Rated current	A	7,9	9,0	9,5	16,0	17,5	23,00	10,61	30,00	12,50	
Minimum fuse	A	10	12	12	20	25	30	15	40	20	
COP at A27/W27		13.13-5.66	13.24-5.84	13.35-6.64	13.64-6.45	13.22-6.21	13.32-6.18	13.32-6.18	13.46-6.28	13.46-6.28	
COP at A15/W25		7.15-4.41	7.22-4.67	7.28-4.52	7.22-4.61	7.21-4.62	7.24-4.65	7.24-4.65	7.28-4.65	7.28-4.65	
COP at A0/W25		3.23-2.83	3.28-2.88	3.34-2.91	3.38-2.97	3.28-2.94	3.31-3.01	3.31-3.01	3.43-3.04	3.43-3.04	
COP at A-5/W25		2.92-2.73	2.96-2.79	3.01-2.79	3.06-2.85	3.04-2.81	3.07-2.88	3.07-2.88	3.11-2.95	3.11-2.95	
Power supply	V/Ph/Hz	220-240/1/ 50	220-240/1/ 50	220-240/1/ 50	220-240/1/ 50	220-240/1/ 50	220-240/1/ 50	380/3/ 50	220-240/1/ 50	380/3/ 50	
Heat exchanger		Twist-titanium tube in PVC									
Compressor brand		Mitsubishi									
Refrigerant		R32	R32	R32	R32	R32	R32	R32	R32	R32	
Fan quantity		1					2				
Fan direction		Horizontal									
Fan speed	RPM	400-700	400-800	400-800	300-750	400-750	400-800	400-800	400-900	400-900	
Power input of Fan	W	40	40	40	75	75	75*2	75*2	75*2	75*2	
Noise level(1m)	dB(A)	38-50	39-51	42-53	42-54	42-55	42-57	42-57	42-58	42-58	
Noise level(10m)	dB(A)	19-29	20-30	22-32	24-33	24-33	26-37	26-37	28-38	28-38	
Water connection	mm	50									
Nominal flow rate	m ³ /h	2,4	3,0	4,9	5,2	6,0	8,6	8,5	10,0	10,0	
Net dimension LxWxH	mm	1000x418x605	1000x418x605	1000x418x605	1046x435x767	1160x470x862	1165x470x1275	1165x470x1275	1165x470x1275	1165x470x1275	

model : min vol 4x heating capacity (A15/W25)
max vol 7x heating capacity (A15/W25)