

X-CORE®

This simple irrigation controller offers optional on-site smart ET watering adjustments and handheld remote operation.

KEY BENEFITS

- Number of stations:
 - 2, 4, 6, or 8 (fixed models)
- Add a Solar Sync® Sensor to save water based on local weather conditions
- Built-in key lock on outdoor models protects against vandalism
- 3 flexible programs with 4 start times each and up to 4-hour run times
- QuickCheck™ Technology provides simple diagnostics of faulty field wiring
- Hide Programs setting shows 1 program and 1 start time for simplification
- Suspend irrigation up to 99 days during the off-season
- Short-circuit protection detects wiring faults and skips the station without system damage
- Easy Retrieve® Memory backs up the full irrigation schedule
- Delay Between Stations for slow-closing valves or pump recharge
- Cycle and Soak prevents water waste and runoff in areas with elevation changes or tight soils
- Seasonal adjustment for quicker schedule adjustments without changing run times

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Sensor inputs: 1
- Approvals: Plastic IP54 (outdoor), UL, cUL, FCC, CE, RCM, ISED
- Warranty period: 2 years



Plastic Indoor

Height: 6½"
Width: 5¾"
Depth: 2"



Plastic Outdoor

Height: 8¾"
Width: 7"
Depth: 3¾"

STANDARD CONTROLLERS

Compatible with:



Solar Sync
Sensor



ROAM Remote
ROAM XL Remote



Soil-Clik
Sensor

X-CORE	
Model	Description
XC-200i	Fixed 2-station, plastic indoor wall mount
XC-400i	Fixed 4-station, plastic indoor wall mount
XC-400	Fixed 4-station, plastic outdoor wall mount with plug
XC-600i	Fixed 6-station, plastic indoor wall mount
XC-600	Fixed 6-station, plastic outdoor wall mount with plug
XC-800i	Fixed 8-station, plastic indoor wall mount
XC-800	Fixed 8-station, plastic outdoor wall mount with plug



EPA WaterSense

Add the WaterSense labeled Solar Sync Sensor to improve the water efficiency of this controller.