

# ProSeries™ HI Side & Top

## THE RELIABLE AND COMPETITIVE SOLUTION

- **Polypropylene mold-injected filters**, for pools up to 65 m<sup>3</sup>
- **Hard-wearing and resistant to intense chemical treatments**
- **Top and side, valve and manometer included**
- **Easy maintenance:** transparent SAN® screw-on cover, easy opening, no tools needed, and laterals quick connect
- **Double-side diffuser** for optimal water spreading over the media
- **Wide Double drain:** water only 1" / water + media 1 1/4"
- **Filter manufactured in Europe**



ProSeries™ HI Side

ProSeries™ HI Top




6-position valve




180 mm diameter threaded opening for simpler maintenance operations



Circular base for perfect filter stability



Dimensions of HI Side filter



Dimensions of HI Top filter

### Technical Specifications

Max. water temperature	50°C
Operating pressure	0.5 - 1.3 bar
Maximum pressure	2.0 bar
Connection	1.5"
Tank / Arms / Unions / Cover	PP/PP/ABS/SAN®, suitable for saltwater
Granulometry of filtration media	0.4 ÷ 0.8 mm

	Flow rate	Diameter ø	In/Out	Filtration area	Empty weight	Sand	Dimensions					Item
							A	B	C	D	E	
PROSERIES™ HI SIDE	6 m <sup>3</sup> /h	400	1" ½	0.13 m <sup>2</sup>	10.5 kg	50 kg	266 mm	391 mm	651 mm	503 mm	453 mm	S160SIE
	9.5 m <sup>3</sup> /h	500	1" ½	0.19 m <sup>2</sup>	12.5 kg	100 kg	345 mm	470 mm	808 mm	503 mm	553 mm	S210SIE
	14 m <sup>3</sup> /h	600	1" ½	0.28 m <sup>2</sup>	15.5 kg	125 kg	391 mm	516 mm	891 mm	503 mm	653 mm	S240SIE
PROSERIES™ HI TOP	6 m <sup>3</sup> /h	400	1" ½	0.13 m <sup>2</sup>	10 kg	50 kg	720 mm	780 mm	922 mm	503 mm	453 mm	S160TIE
	9.5 m <sup>3</sup> /h	500	1" ½	0.19 m <sup>2</sup>	12 kg	100 kg	877 mm	937 mm	1079 mm	503 mm	553 mm	S210TIE
	14 m <sup>3</sup> /h	600	1" ½	0.28 m <sup>2</sup>	15 kg	125 kg	960 mm	1020 mm	1161 mm	503 mm	653 mm	S240TIE