


COD. 21.65 - COD. 21.66

ELECTROFUSION TRANSITION 90° ELBOW WITH BRASS INSERT

MALE SDR 7,4 - PN 25



DIMENSIONS							WEIGHTS	
dn	G	de	L	h	Z	Ch		
20	½"	34	33	20	81	22	105	
25	¾"	38	33	21	83	27	125	
32	1"	46	39	26	106	34	285	
40	1" ¼	56	48	29	114	42	455	
50	1" ½	68	54	33	129	52	705	
63	2"	83	52	37	151	65	1120	
75	2" ½	97	64	43	169	86	1725	
90	3"	116	70	46	190	97	2635	
110	4"	142	76	52	210	125	3865	


Ch = tightening key size

WELDABILITY ON PIPE/FITTING PE 100

dn	SDR 17	SDR 11	SDR 9	SDR 7,4
20		● ▲	● ▲	●
25		● ▲	●	●
32	● ▲	●	●	●
40	● ▲	●	●	●
50	●	●	●	●
63	●	●	●	●
75	●	●	●	●
90	●	●	●	●
110	●	●	●	●

● weldable only with monovalent welding units Series Euro
▲ minimum weldable thickness 3 mm

FEMALE SDR 7,4 - PN 25



DIMENSIONS							WEIGHTS	
dn	G	de	L	h	Z	Ch		
20	½"	34	33	18	79	27	160	
25	¾"	38	33	20	82	34	220	
32	1"	46	39	22	102	40	310	
40	1" ¼	56	48	27	111	50	525	
50	1" ½	68	54	27	121	55	735	
63	2"	83	52	33	147	67	1105	
75	2" ½	97	64	39	165	86	1735	
90	3"	116	70	42	186	97	2575	
110	4"	142	76	48	206	125	4125	

Ch = tightening key size

WELDABILITY ON PIPE/FITTING PE 100

dn	SDR 17	SDR 11	SDR 9	SDR 7,4
20		● ▲	● ▲	●
25		● ▲	●	●
32	● ▲	●	●	●
40	● ▲	●	●	●
50	●	●	●	●
63	●	●	●	●
75	●	●	●	●
90	●	●	●	●
110	●	●	●	●

● weldable only with monovalent welding units Series Euro
▲ minimum weldable thickness 3 mm

- During the screwing, lock the metallic hexagon to avoid any stress on the PE part
- Suitable for gas and water pipelines
- Do not remove the insert