

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 30 (replaces version 29) Revision: 11.11.2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GRF CLEANER PVC TI 1L\*6 L127
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Bison International B.V.

Dr.A.F.Philipsstraat 9

NL-4462 EW Goes

PO Box 160

NL-4460 AD Goes

tel. +31 88 3235700

fax. +31 88 3235800

e mail: sds@boltonadhesives.com

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms





GHS02 GHS07

· Signal word Danger

(Contd. on page 2)

GB

www.griffon.eu 1/12



## Safety data sheet

## according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 30 (replaces version 29) Revision: 11.11.2024

Trade name: GRF CLEANER PVC TI 1L\*6 L127

(Contd. of page 1)

## · Hazard-determining components of labelling:

Ethyl acetate

Butanone

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection / face protection.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

## Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Labelling of packages where the contents do not exceed 125 ml

· Hazard pictograms





GHS02 GHS07

## · Signal word Danger

## · Hazard-determining components of labelling:

Ethyl acetate

Butanone

### · Hazard statements

H336 May cause drowsiness or dizziness.

## **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection / face protection.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with national regulations.

## 2.3 Other hazards

## · Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## · Determination of endocrine-disrupting properties

78-93-3 Butanone

List II

(Contd. on page 3)

www.griffon.eu 2/12



## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 30 (replaces version 29) Revision: 11.11.2024

Trade name: GRF CLEANER PVC TI 1L\*6 L127

(Contd. of page 2)

## **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Cleansing agent

| · Dangerous components:  |  |         |
|--|--|---------|
| CAS: 141-78-6<br>EINECS: 205-500-4<br>Index number: 607-022-00-5<br>Reg.nr.: 01-2119475103-46-<br>XXXX | Ethyl acetate  Flam. Liq. 2, H225; Description Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 | 50-100% |
| CAS: 78-93-3<br>EINECS: 201-159-0<br>Index number: 606-002-00-3<br>Reg.nr.: 01-2119457290-43-<br>XXXX  | Butanone  String Flam. Liq. 2, H225; String Eye Irrit. 2, H319; STOT SE 3, H336, EUH066    | 25-50%  |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

Supply fresh air; consult doctor in case of complaints.

No special measures required.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Water haze

Alcohol resistant foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- Additional information

Cool endangered receptacles with water spray.

(Contd. on page 4)

GB -

www.griffon.eu 3/12



## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 30 (replaces version 29) Revision: 11.11.2024

Trade name: GRF CLEANER PVC TI 1L\*6 L127

(Contd. of page 3)

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### **SECTION 6: Accidental release measures**

## · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

## · 8.1 Control parameters

## · Ingredients with limit values that require monitoring at the workplace:

## 141-78-6 Ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

#### 78-93-3 Butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

(Contd. on page 5)

GB

www.griffon.eu 4/12



# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 30 (replaces version 29) Revision: 11.11.2024

Trade name: GRF CLEANER PVC TI 1L\*6 L127

| DNE! -  |                        |                                     |                   | (Contd. of p |
|---|------------------------|-------------------------------------|-------------------|--------------|
| DNELs   | C Ethani a a a tata    |                                     |                   |              |
|   | 6 Ethyl acetate        | antama aynaaitian                   | 4.5 mg/kg bw/day  |              |
| Oral  |                        | Consumer, oral, longterm exposition |                   |              |
| Dermal  | Worker, dermal, lo     | •                                   | 63 mg/kg bw/day   |              |
|   |                        | longterm exposition                 | 37 mg/kg bw/day   |              |
| Inhalativ   |                        | shortterm exposition                | 1468 mg/m³        |              |
|   |                        | longterm exposition                 | 734 mg/m³         |              |
|   | Consumer DNEL, a       |                                     | 734 mg/m³         |              |
|   |                        | ve, longterm exposition             | 367 mg/m³         |              |
|   | Butanone               |                                     |                   |              |
| Oral  | Consumer, oral, lo     | •                                   | 31 mg/kg bw/day   |              |
| Dermal  | Worker, dermal, lo     | •                                   | 1161 mg/kg bw/day |              |
|   |                        | longterm exposition                 | 412 mg/kg bw/day  |              |
| Inhalativ   |                        | shortterm exposition                | 900 mg/m³         |              |
|   | Worker, inhalative,    | longterm exposition                 | 600 mg/m³         |              |
|   | Consumer DNEL, a       | acute inhalation                    | 450 mg/m³         |              |
|   | Consumer, inhalati     | ve, longterm exposition             | 106 mg/m³         |              |
| PNECs   |                        |                                     |                   |              |
| 141-78-   | 6 Ethyl acetate        |                                     |                   |              |
| Fr  | esh water              | 0.24 mg/l                           |                   |              |
| Fr  | esh water sediment     | 1.15 mg/kg dry weight               |                   |              |
| Ma  | arine water            | 0.024 mg/l                          |                   |              |
| Ma  | arine sediment         | 0.115 mg/kg dry weight              |                   |              |
| Sc  | oil                    | 0.148 mg/kg                         |                   |              |
| Se  | ewage treatment plant  |                                     |                   |              |
| 78-93-3   | Butanone               | -                                   |                   |              |
| Oral Se   | econdary Poisoning     | 1000 mg/kg                          |                   |              |
| Fr  | esh water              | 55.8 mg/l                           |                   |              |
| Fr  | esh water sediment     | 284.7 mg/kg dry weigh               | t                 |              |
| Ma  | arine water            | 55.8 mg/l                           |                   |              |
| Ma  | arine sediment         | 284.7 mg/kg dry weigh               | t                 |              |
| Sc  | oil                    | 22.5 mg/kg                          |                   |              |
| Se  | ewage treatment plant  |                                     |                   |              |
|   | ooradic release        | 55.8 mg/l                           |                   |              |
| Ingredi   | ents with biological I |                                     |                   |              |
|   | Butanone               |                                     |                   |              |
| BMGV  | BMGV 70 µmol/L         |                                     |                   |              |
|   | Medium: urine          |                                     |                   |              |
| Sampling time: post shift   |                        |                                     |                   |              |
| Parameter: butan-2-one  Additional information: The lists valid during the making were used as basis. |                        |                                     |                   |              |

www.griffon.eu 5/12

(Contd. on page 6)



## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 30 (replaces version 29) Revision: 11.11.2024

Trade name: GRF CLEANER PVC TI 1L\*6 L127

(Contd. of page 5)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

- · Recommended filter device for short term use: Filter A
- Hand protection

Solvent resistant gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Butyl rubber, BR

Nitrile rubber, NBR

Recommended thickness of the material: > 0,7 mm

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

For the mixture of chemicals mentioned below the penetration time has to be at least 120 minutes (Permeation according to EN 374 Part 3: Level 4).

· Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

Body protection: Solvent resistant protective clothing

## **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

· General Information

· Physical state Flu

Colour: According to product specification

Odour: Characteristic

(Contd. on page 7)

GB

www.griffon.eu 6/12



## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 30 (replaces version 29) Revision: 11.11.2024

Trade name: GRF CLEANER PVC TI 1L\*6 L127

(Contd. of page 6)

Odour threshold: Not determined.Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and

boiling range 77-78 °C

· Flammability Highly flammable.

· Lower and upper explosion limit

Lower: 1.8 Vol %
Upper: 11.5 Vol %
Flash point: -9 °C
Auto-ignition temperature: 460 °C

Decomposition temperature: Not determined. pH Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 0.42 mPas

Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log

value) Not determined.
• Vapour pressure at 20 °C: 105 hPa

• Vapour pressure at 50 °C: 360 hPa
• Density and/or relative density

Density at 20 °C:
Relative density

Vapour density

0.858-0.86 g/cm³
Not determined.

Not determined.

• 9.2 Other information All relevant physical data were determined for the

mixture. All non-determined data are not measurable or not relevant for the

characterization of the mixture.

· Appearance:

· Form: Fluid

Important information on protection of health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· Organic solvents: 100.0 % · Solids content: 0.0 %

Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard

classes

Explosives
Flammable gases
Aerosols
Oxidising gases
Gases under pressure
Void
Void

• Flammable liquids Highly flammable liquid and vapour.

(Contd. on page 8)

GB

www.griffon.eu 7/12



## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 30 (replaces version 29) Revision: 11.11.2024

Trade name: GRF CLEANER PVC TI 1L\*6 L127

(Contd. of page 7)

|                                       |      | (Conta. or page 1) |
|---------------------------------------|------|--------------------|
| · Flammable solids                    | Void |                    |
| Self-reactive substances and mixtures | Void |                    |
| · Pyrophoric liquids                  | Void |                    |
| Pyrophoric solids                     | Void |                    |
| Self-heating substances and mixtures  | Void |                    |
| Substances and mixtures, which emit   |      |                    |
| flammable gases in contact with water | Void |                    |
| Oxidising liquids                     | Void |                    |
| Oxidising solids                      | Void |                    |
| Organic peroxides                     | Void |                    |
| Corrosive to metals                   | Void |                    |
| · Desensitised explosives             | Void |                    |
|                                       |      |                    |

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Danger of forming toxic pyrolysis products.

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 values relevant for classification: |                        |                       |  |
|---|------------------------|-----------------------|--|
| 141-78-6 I                                    | 141-78-6 Ethyl acetate |                       |  |
| Oral  | LD50                   | 4934 mg/kg (rabbit)   |  |
| Dermal  | LD50                   | >20000 mg/kg (rabbit) |  |
| Inhalative                                    | LC50/4 h               | 29.3 mg/l (rat)       |  |
| 78-93-3 B                                     | 78-93-3 Butanone       |                       |  |
| Oral  | LD50                   | >2193 mg/kg (rat)     |  |
| Dermal  | LD50                   | >8050 mg/kg (rat)     |  |

- · **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.

(Contd. on page 9)

GΒ

www.griffon.eu 8/12



## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 30 (replaces version 29) Revision: 11.11.2024

Trade name: GRF CLEANER PVC TI 1L\*6 L127

(Contd. of page 8)

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- · Repeated dose toxicity Not applicable.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

78-93-3 Butanone

List II

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

## **SECTION 14: Transport information**

- · 14.1 UN number or ID number
- ADR/ADN, IMDG, IATA UN1993

(Contd. on page 10)

GB

www.griffon.eu 9/12



# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 30 (replaces version 29) Revision: 11.11.2024

Trade name: GRF CLEANER PVC TI 1L\*6 L127

|  | (Contd. of page  |
|--|--|
| 14.2 UN proper shipping name<br>ADR/ADN<br>IMDG, IATA        | 1993 FLAMMABLE LIQUID, N.O.S. (ETHY ACETATE, ETHYL METHYL KETONE (METHY ETHYL KETONE)), special provision 640D FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATI ETHYL METHYL KETONE (METHYL ETHY KETONE)) |
| 14.3 Transport hazard class(es)                              |  |
| ADR/ADN  |  |
| 3  |  |
| Class<br>Label   | 3 (F1) Flammable liquids.  |
| IMDG, IATA   | <b>J</b>   |
|  | 2 Flammable limida   |
| Class<br>Label   | 3 Flammable liquids.   |
| 14.4 Packing group<br>ADR/ADN, IMDG, IATA                    | II   |
| 14.5 Environmental hazards:<br>Marine pollutant:             | No   |
| 14.6 Special precautions for user                            | Warning: Flammable liquids.  |
| Hazard identification number (Kemler code): EMS Number:      | 33<br>F-E,S-E  |
| Stowage Category   | г- <u>с,о-с</u><br>В   |
| 14.7 Maritime transport in bulk according to IMO instruments | Not applicable.  |
| Transport/Additional information:                            |  |
| Quantity limitations   | On passenger aircraft/rail: 5 L  |
|  | On cargo aircraft only: 60 L   |
| ADR/ADN  | 41   |
| Limited quantities (LQ) Excepted quantities (EQ)             | 1L<br>Code: E2   |
| · · · · · ·  | Maximum net quantity per inner packaging: 30 m<br>Maximum net quantity per outer packaging: 50<br>ml   |
| Transport category   | 2  |
| Tunnel restriction code                                      | D/E  |

www.griffon.eu 10/12



## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 11.11.2024 Version number 30 (replaces version 29) Revision: 11.11.2024

Trade name: GRF CLEANER PVC TI 1L\*6 L127

(Contd. of page 10) ·IMDG · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 · Remarks: For substances with class 3 according to IMDG-Code chapter 2.3.2.2 packing group is classified in packing group III, as viscosity is in accordance with requirements (flow time t > 100s). · UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, ETHYL METHYL KETONE (METHYL ETHYL KETONE)), 3, II

## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements  $50000\ t$
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Regulation (EC) No 273/2004 on drug precursors

78-93-3 Butanone

3

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

78-93-3 Butanone

(Contd. on page 12)

www.griffon.eu 11/12



## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 11.11.2024 Printing date 11.11.2024 Version number 30 (replaces version 29)

Trade name: GRF CLEANER PVC TI 1L\*6 L127

(Contd. of page 11)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

| · Classification according to Regulation (EC) No 1272/2008 |  |  |
|--|--|--|
| Flammable liquids  | Bridging principles  |  |
| Specific target organ toxicity (single exposure)           | The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. |  |

· Department issuing SDS: PSRA

· Contact: PSRA

Date of previous version: 01.08.2024 · Version number of previous version: 29

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

12/12 www.griffon.eu