

# KORAL-KSE

THE ORIGINAL

CLASSIC LINE

YEARS OF WARRANTY | 2



- ➔ Optimised and super-silent hydraulic system
- ➔ Visibility of the internal prefilter, easy access
- ➔ Impeller in corrosion-resistant and hard-wearing Noryl®
- ➔ Double drain, easy opening (no tools required)
- ➔ Connections: ANSI 1½-2", includes slip unions for Ø 50 and Ø 63 mm
- ➔ Suitable for use in salt water
- ➔ **Usage: for residential pools up to 177 m³**

	Code	Ref.	P2 Hp	P1 kW	A (mm)	Flow rate (m³/h)*	Weight (kg)	Pack. (mm)	qty/pallet	M.O.Q**	
SINGLE PHASE	010401221010	KSE 33 M	0,33	0,45	503	4,8	11,2	330 x 255 x 650	25	1	
	010411320110	KSE 50 M	0,50	0,58	550	7,5	12,5	330 x 255 x 650	25	1	
	010411420110	KSE 75 M	0,75	0,75	550	11,5	13,5	330 x 255 x 650	25	1	
	010411520110	KSE 100 M	1,00	1	550	15,4	14	330 x 255 x 650	25	1	
	010421120120	KSE 150 M	1,50	1,6	580	21,9	16,5	330 x 255 x 650	25	1	
	010421220120	KSE 200 M	2,00	1,92	580	25,7	17,5	330 x 255 x 650	25	1	
010421420120	KSE 300 M	3,00	2,6	620	29,5	22,5	330 x 255 x 650	25	1		
THREE PHASE	010411350110	KSE 50 T1	0,50	0,58	550	7,5	12	330 x 255 x 650	25	1	
	010411450110	KSE 75 T1	0,75	0,75	550	11,5	13	330 x 255 x 650	25	1	
	010471050110	KSE 100 T1 IE3	1,00	1	550	15,4	13,5	330 x 255 x 650	25	1	IE3 ✓
	010471150110	KSE 150 T1 IE3	1,50	1,6	580	21,9	16	330 x 255 x 650	25	1	IE3 ✓
	010481250110	KSE 200 T1 IE3	2,00	1,92	580	25,7	17	330 x 255 x 650	25	1	IE3 ✓
	010481350110	KSE 300 T1 IE3	3,00	2,06	620	29,5	22	330 x 255 x 650	25	1	IE3 ✓

P1: Input Power

P2: Nominal Power

\* 10 m water column pressure


\*\* (minimum order quantity)

60 Hz on request, ask for conditions; ANSI or JIS on request

NEW

**LTRK Smart retrofit kit: use it with the KSE VS to replace easily old pumps on existing installations**

Item	Pumps to replace	Kit content	Kit per box
LTRK	Astral Victoria Plus, Astral Victoria Plus Silent	Smart Base (1), Fixing screw (3), RC50 (2), O-ring Seal (2)	10



### Technical Specifications

Max. water temp. / Max. pressure	50°C / 2,5 bar
Connection (DIN slip included, for others please ask)	Ø 50 - 1 ½" (0,33-1 hp) / Ø 63 - 2" (1,5-3,00 hp)
Mechanical seal	AISI 316, suitable for salt water
Motor specifications	Class F, IP55, 50 Hz 2.850 rpm
Housing/impeller/strainer/lid	PP + F.G/Noryl®/PP/SAN®

