

VGE Pro UV INOX

Part nr	Model	Shape	Max. pressure [bar]	Connection	Capacity ⁽¹⁾ [m ³ /h]	Water quality ⁽²⁾			Aqua- culture	Agri- & Horti- culture	Food & Process- industry	Drinking- water	Swimming ponds	Swimming
						good	medium	bad						
	400-54	Z	6 bar	1"	18		✓	✓	✓		✓	✓	✓	✓
	40-76	L	6 bar	3/4"	3	✓	✓		✓	✓	✓	✓	✓	✓
	75-76	L	6 bar	1 1/2"	6		✓		✓	✓	✓	✓	✓	✓
7029947	140-76	U	6 bar	1 1/2"	12	✓	✓		✓	✓	✓	✓	✓	✓
7029948	200-76	U	6 bar	2"	17	✓	✓		✓	✓	✓	✓	✓	✓
	75-114	U	6 bar	2"	10	✓	✓		✓	✓	✓	✓	✓	✓
	140-114	U	6 bar	2"	20	✓	✓		✓	✓	✓	✓	✓	✓
7029949	200-154	U	6 bar	DN80	38	✓			✓	✓	✓	✓	✓	✓
7029950	420-168	U	6 bar	3"	78	✓	✓		✓	✓	✓	✓	✓	✓
7029951	400-204	U	6 bar	DN100	92	✓			✓	✓	✓	✓	✓	✓
7029952	600-219	U	6 bar	DN125	140	✓			✓	✓	✓	✓	✓	✓
7029953	975-306	L	6 bar	DN250	306	✓			✓	✓	✓	✓	✓	✓
7029954	1950-306	L	6 bar	DN250	600	✓			✓	✓	✓	✓	✓	✓

⁽¹⁾ Capaciteit op basis van 400 J/m², T_{10 mm @ 254 nm} = 98 %, MPSSM-gemiddelde intensiteit (max. stroomsnelheid van 3 m/s niet meegenomen)

⁽²⁾ Waterkwaliteit op basis van watertransmissie, T_{10 mm @ 254 nm}: goed = 100 % - 80 %, Medium = 80 % - 50 %, Slecht < 50 %